# FLOS

### LIGHT SHADOW ADJUSTABLE TRIM DALI VERSION 8 SPOTS OPTIC FLOOD

Mounting Lamps description Luminaire luminous flux Environment Notes

Ceiling recessed Power LED 21,6W 2240 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame not required.

### OPTICAL

Aiming Light distribution symmetry **Beam angle** 

#### ELECTRICAL

- **Transformer availability Transformer mounting** Transformer type Emergency Insulation class
- Included Remote Electronic dimmable dali Without Class II

#### PHYSICAL

Recessed depth (mm)	
Weight (kg)	

75 0,50

Adjustable

Symmetric

33° Flood







designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

🖉 03.9355.40.DA - 1682lm	White / White
03.9355.14.DA - 1682lm	Black / White
align 3.9357.40.DA - 1720lm	White / Chrome
03.9357.14.DA - 1720lm	Black / Chrome
🥖 03.9358.40.DA - 1667lm	White / Matt Gold
💋 03.9358.14.DA - 1667lm	Black / Matt Gold
03.9356.40.DA - 1634lm	White / Black
03.9356.14.DA - 1634lm	Black / Black



CERTIFICATIONS GWT CE PENDING F 850° IP 4 ) € 44 10-100% 30° 30°



# FLOS

## Light Shadow Adjustable Trim Dali Version 8 Spots Optic Flood . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

🖉 03.9355.40.DA - 1682lm	White / White
Ø3.9355.14.DA - 1682lm	Black / White
a3.9357.40.DA - 1720lm	White / Chrome
03.9357.14.DA - 1720lm	Black / Chrome
🥖 03.9358.40.DA - 1667lm	White / Matt Gold
Ø3.9358.14.DA - 1667lm	Black / Matt Gold
🟉 03.9356.40.DA - 1634lm	White / Black
03.9356.14.DA - 1634lm	Black / Black

