# FLOS

### LIGHT SHADOW ADJUSTABLE TRIM DALI VERSION 12 SPOTS OPTIC FLOOD

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 32,4W 3360 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame not required.

### OPTICAL

Aiming Light distribution symmetry Beam angle

#### ELECTRICAL

- Transformer availability Transformer mounting Transformer type Emergency Insulation class
- Included Remote Electronic dimmable dali Without Class II

#### PHYSICAL

Recessed depth (mm)	
Weight (kg)	

75 0,66

Adjustable

Symmetric

33° Flood








designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9375.40.DA - 2523lm	White / White
03.9375.14.DA - 2523lm	Black / White
aligned 3.9377.40.DA - 2580lm	White / Chrome
03.9377.14.DA - 2580lm	Black / Chrome
🥖 03.9378.40.DA - 2500lm	White / Matt Gold
💋 03.9378.14.DA - 2500lm	Black / Matt Gold
03.9376.40.DA - 24511m	White / Black
03.9376.14.DA - 24511m	Black / Black







# FLOS

## Light Shadow Adjustable Trim Dali Version 12 Spots Optic Flood . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



🖉 03.9375.40.DA - 2523lm	White / White
• 03.9375.14.DA - 2523lm	Black / White
a3.9377.40.DA - 2580lm	White / Chrome
03.9377.14.DA - 2580lm	Black / Chrome
🥖 03.9378.40.DA - 2500lm	White / Matt Gold
<b>Ø</b> 03.9378.14.DA - 2500lm	Black / Matt Gold
🕑 03.9376.40.DA - 24511m	White / Black
03.9376.14.DA - 24511m	Black / Black

