

LIGHT SHADOW ADJUSTABLE NO TRIM DALI VERSION 2 SPOTS OPTIC FLOOD

Mounting Ceiling recessed

Lamps descriptionPower LED 5,4W 520 Im 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 33° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Recessed depth (mm)
 75

 Weight (kg)
 0,25






Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9405.40.DA - 394lm White / White 03.9405.14.DA - 394lm Black / White 03.9407.40.DA - 403lm White / Chrome 03.9407.14.DA - 403lm Black / Chrome → 03.9408.40.DA - 390lm White / Matt Gold 03.9408.14.DA - 390lm Black / Matt Gold ● 03.9406.40.DA - 383lm White / Black 03.9406.14.DA - 383lm Black / Black



CERTIFICATIONS






















Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood . Accessories

Mounting





08.0515.00

08.0059.90

Pre-installation frame. Adjustable No Trim 2L Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

$\textbf{Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood}. \ \textbf{Lamps}$



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9405.40.DA - 394lm White / White 03.9405.14.DA - 394lm Black / White 03.9407.40.DA - 403lm White / Chrome 03.9407.14.DA - 403lm Black / Chrome 03.9408.40.DA - 390lm White / Matt Gold 03.9408.14.DA - 390lm Black / Matt Gold ■ 03.9406.40.DA - 383lm White / Black 03.9406.14.DA - 383lm Black / Black



CERTIFICATIONS

















