FLOS

SUPER LINE DOWN

Number of heads

Mounting Pendant

Lamps description Top LED 38,6W 4488 lm 3000K CRI 90

Environment Indoor

OPTICAL

AimingFixedLight distribution symmetrySymmetricBeam angle76°

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic, Electronic dimmable dali

Emergency Without Insulation class Class III

PHYSICAL

Length (mm) 1500

Construction material Extruded aluminum

Weight (kg) 1,45






Super Line Down designed by FLOS Architectural

<div>LED luminaire for general lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

03.9510.40 - 3571lm White
03.9510.02 - 3571lm Grey
03.9510.14 - 3571lm Black



CERTIFICATIONS

















Super Line Down . Accessories

Electrical














div>




08.0520.02



Recessed Kit. 60W – 110/220V Power Supply Included Non Dimmable

08.0522.14



ceilings by means of suspension. Power source included in installation kits must be ordered separately.</








08.0525.40

08.0525.02

08.0525.14





08.0523.40 08.0523.02 08.0523.14

Remote Power Supply Kit. 60W – I I 0/220V Power Supply Included Non Dimmable

08.0524.02

08.0524.14

Remote Power Supply Kit. 60W – I 10/220V Power Supply Included Dali Version

CERTIFICATIONS




















Super Line Down . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:


Top LED



Super Line Down designed by FLOS Architectural

<div>LED luminaire for general lighting with a signature minimalist and compact design, to be installed on ceilings by means of suspension. Power source included in installation kits must be ordered separately.

03.9510.40 - 3571lm	White
03.9510.02 - 3571lm	Grey
03.9510.14 - 3571lm	Black



CERTIFICATIONS













