

G-O AMBER LIGHT

Number of heads	1
Mounting	Wall recessed
Lamps description	Top LED 1,2W 105 lm 3000K CRI 90
Luminaire luminous flux	See reference number
Voltage (V)	24
Environment	Indoor, Outdoor
Notes	Embedded light fixture for indoor use in all its finishes, except stainless steel which is suitable for outdoor use. Equipment (60.8495) for remote installation in an accessible place: it does not fit through the luminaire installation hole.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	72°

ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic, Electronic dimmable dali
Emergency	Without
Insulation class	Class III

PHYSICAL


Cutout diameter (mm)	40
Diameter (mm)	44
Recessed depth (mm)	56
Construction material	Aluminium or Bronze or Stainless steel
Weight (kg)	0,20




G-O Amber Light designed by Jorge Herrera

Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

09.3201.30A - 11m	White
09.3201.29A - 11m	Anodised aluminium
09.3201.55A - 11m	Stainless steel
09.3201.BZA - 11m	Bronze
09.3201.ANA - 11m	Anodised aluminium / Black



CERTIFICATIONS



G-O Amber Light . Accessories

Power Supply



60.8495

Electronic transformer with constant voltage (24V) for LED. 20W

Electronic transformer with constant voltage (24V) for LED. 100/240V.

Maximum lenght of 1.5 mm2 secondary conductor (m): 5



60.9157

Electronic transformer with constant voltage (24V) for LED. 8W

Electronic transformer with constant voltage (24V) for LED. 8W. 90/264V.

Maximum lenght of 1.5 mm2 secondary conductor (m): 5

Mounting



08.8422.00

Prepared for recessing


Housing for recessed installation made in anodized aluminium for outdoor installation.



G-O Amber Light designed by Jorge Herrera

Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

09.3201.30A - 11m	White
09.3201.29A - 11m	Anodised aluminium
09.3201.55A - 11m	Stainless steel
09.3201.BZA - 11m	Bronze
09.3201.ANA - 11m	Anodised aluminium / Black



CERTIFICATIONS



G-O Amber Light . Accessories

Electrical



60.8635

Dimmable Dali control unit
with 1 channel for 24V LED
modules
Power supply not included.

G-O Amber Light . Lamps



Top LED

Lamp category:
LED

Socket:
Special base


Lamp type:
Top LED



G-O Amber Light designed by Jorge Herrera

Semi recessed signalling lamp for
indoor use on ceiling/wall. Power
supply not included. 1000 mm power
cable included.

09.3201.30A - 11m	White
09.3201.29A - 11m	Anodised aluminium
09.3201.55A - 11m	Stainless steel
09.3201.BZA - 11m	Bronze
09.3201.ANA - 11m	Anodised aluminium / Black



CERTIFICATIONS

