

UT DOWNLIGHT NO TRIM Ø86 DALI VERSION

Number of heads

Mounting Ceiling recessed

Lamps description LED Array High Performances 27W 2656 lm 3000K CRI 90

Luminaire luminous flux See reference number

Voltage (V) 220/240 Environment Indoor

Notes Pre-installation frame must be ordered separately.

OPTICAL

Reflector finishAluminumAimingAdjustableLight distribution symmetrySymmetricBeam angle12° Spot

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

EmergencyWithoutInsulation classClass II

PHYSICAL

Cutout diameter (mm) 132 Spot diameter (mm) 86

Construction material Aluminium Weight (kg) 0,97






UT Downlight No Trim Ø86 Dali Version designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>

09.4922.30ADA - 1866lm White 09.4922.14ADA - 1866lm Black



CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com



UT Downlight No Trim Ø86 Dali Version . Accessories

Mounting



08.8995.30

08.8995.14

Installation frame NO TRIM



UT Downlight No Trim Ø86 Dali Version designed by FLOS Architectural

Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>


09.4922.30ADA - 1866lm White 09.4922.14ADA - 1866lm Black

Optical









08.8163.68

Elliptical lens

Elliptical light distribution lens in 4 mm thick tempered glass.

08.8175.68

Flood lens

Flood lens made in press glass.

08.8495.14

Honeycomb

"Honeycomb" anti-glare screen: in thin, black-painted aluminium sheets. CERTIFICATIONS



900











GWT

850°

Flos.architectural@flos.com www.flos.com



UT Downlight No Trim Ø86 Dali Version . Accessories







08.8411.00

Holding ring

Screening crosspiece

Holding ring


Recessed luminaire with LED light source. 220-240V, 50-60Hz remote power supply included.<nextline>

09.4922.30ADA - 1866lm White 09.4922.14ADA - 1866lm Black

UT Downlight No Trim Ø86 Dali Version

designed by FLOS Architectural

UT Downlight No Trim Ø86 Dali Version . Lamps





LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:

LED Array

CERTIFICATIONS

















Flos.architectural@flos.com www.flos.com