


Kelvin Led Wall support

By instable wall-dam were triding udirest 1,200,99, with double pantograph arm and adjustable head. Fused aluminum alloy body. Die-cast aluminum outer head, with injection-molded methacrylate diffuser. Painted CNC machined, extruded aluminum WALL FITTING. Extruded aluminum alloy square tube (12x12mm) structure, machined mechanically, so that it houses a stainless steel load-compensation spring and injection-molded acetal resin sliding blocks. 3 mm diameter wire outer tie rods. Available in white, anthracite, black or chrome finishes. The ON/ OFF switch is electronic with optical mechanism located in the head.

Two possibilities to choose:

- PERSONAL MODE (orange switch) Dimm the light intensity you
- GREEN MODE (green switch) Now Kelvin LED becomes Green, saving even more energy thanks to his automatic compensation of the ambience light.







Mounting Wall arm Environment Indoor

Finish Anthracite, White, Chrome, Black

Weight 1.5 Kg

Light sources 30 x TOP LED 7,5W Green Mode 3000K CRI95 available

Without Emergency 100-240/24V Voltage

8W Power Nο **Battery** Supply included Yes

1800 mm Cord Length Materials Aluminum

Colors F3302030 - Shiny black

> F3302009 - Shiny white F3302033 - Anthracite F3314057 - Chrome