

## **USL 1000 DIMMABLE DSI-DALI**

Lamps description 4 x T5 FQ G5 39W 12400 lm

**Environment** Indoor

**OPTICAL** 

Aiming Fixed

#### **ELECTRICAL**

Control gear availability Included


Control gear type Electronic dimmable Dsi & dali

Emergency Without Insulation class Class I

# **USL 1000 Dimmable DSI-Dali** designed by FLOS Soft Architecture

Indirect ceiling-mounted lighting system. Indirect lighting for linear fluorescent lamps. It permits installation of Flos architectural product. Suspension cable length 4 meters.





## **PHYSICAL**

Weight (kg) 16,5



### **CERTIFICATIONS**



IP 20







info@flos.it www.flos.com



## USL 1000 Dimmable DSI-Dali . Lamps



T5 FQ 39W G5

Lamp Watt:

39 W

Lamp category:


Fluorescent tube

Socket:

G5

Lamp type:


T5 FQ



**USL 1000 Dimmable DSI-Dali** designed by FLOS Soft Architecture

Indirect ceiling-mounted lighting system. Indirect lighting for linear fluorescent lamps. It permits installation of Flos architectural product. Suspension cable length 4 meters.

SA.4001.4.2DA Raw



#### **CERTIFICATIONS**







