

# FLOS

## USL 1400 DIMMABLE I-10V

**Lamps description** 4 x T5 FH G5 21W 10400 lm  
**Environment** Indoor

---

### OPTICAL

**Aiming** Fixed

---



### ELECTRICAL

**Control gear availability** Included  
**Control gear type** Electronic dimmable I-10V  
**Emergency** Without  
**Insulation class** Class I

---

### PHYSICAL

**Weight (kg)** 23,1



### USL 1400 Dimmable I-10V designed by FLOS Soft Architecture


---

Indirect ceiling-mounted lighting system. Indirect lighting for linear fluorescent lamps. It permits installation of Flos architectural product. Suspension cable length 4 meters.

---

● SA.4002.4.I1V Raw

---



### CERTIFICATIONS



## USL 1400 Dimmable I-10V . Lamps



FH

### T5 FH 21W G5

**Lamp Watt:**

21 W

**Lamp category:**


Fluorescent tube

**Socket:**

G5

**Lamp type:**


T5 FH



### USL 1400 Dimmable I-10V designed by FLOS Soft Architecture

Indirect ceiling-mounted lighting system. Indirect lighting for linear fluorescent lamps. It permits installation of Flos architectural product. Suspension cable length 4 meters.

● SA.4002.4.11V Raw



### CERTIFICATIONS

