FLOS

WALL PIERCING 1X

Lamps description	LED White 1 x 6,4W 416 lm 2700K CRI>90
Environment	Indoor
Notes	LED modules included. For power supply and dimming interface see LED drivers (downloads).

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric

ELECTRICAL

Control gear availability	Included
Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic
Emergency	Without
Insulation class	Class III

PHYSICAL

|	
Weight (kg)	4

Wall Piercing 1x
designed by Ron Gilad

Soft technology semi-recessed luminaire for ceiling or wall mounting. Available in white LED or RGB versions. Control gear not included.

SA.5020.5A120 White

SA.5020.5A180 Aluminium

Dimensions

600
370
264
600
243
y
y= 55

CERTIFICATIONS

CE | F | III | IP 20

FLOS

Wall Piercing 1x . Lamps

LED White 6.4W

Lamp Watt:
6.4 W

Lamp category:
LED

**Color temperature (K):**
2700 °K

Lamp type:
LED White

Wall Piercing 1x
designed by Ron Gilad

Soft technology semi-recessed luminaire for ceiling or wall mounting. Available in white LED or RGB versions. Control gear not included.

◯ SA.5020.5A120 White

◗ SA.5020.5A180 Aluminium

600
370   264
600   243
y
y= 55

CERTIFICATIONS

CE   ⟨F⟩   ⟨III⟩   IP 20