


IN-FINITY 100 SUSPENSION DOWN 3000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



●	N10D053G30.DA 565mm - 1578lm	White
●	N10D053G02.DA 565mm - 1578lm	Anodized Grey
●	N10D053G14.DA 565mm - 1578lm	Black
●	N10D083G30.DA 845mm - 2367lm	White
●	N10D083G02.DA 845mm - 2367lm	Anodized Grey
●	N10D083G14.DA 845mm - 2367lm	Black
●	N10D113G30.DA 1125mm - 3156lm	White
●	N10D113G02.DA 1125mm - 3156lm	Anodized Grey
●	N10D113G14.DA 1125mm - 3156lm	Black
●	N10D143G30.DA 1405mm - 3945lm	White
●	N10D143G02.DA 1405mm - 3945lm	Anodized Grey
●	N10D143G14.DA 1405mm - 3945lm	Black
●	N10D163G30.DA 1690mm - 4734lm	White
●	N10D163G02.DA 1690mm - 4734lm	Anodized Grey
●	N10D163G14.DA 1690mm - 4734lm	Black
●	N10D193G30.DA 1970mm - 5523lm	White
●	N10D193G02.DA 1970mm - 5523lm	Anodized Grey
●	N10D193G14.DA 1970mm - 5523lm	Black
●	N10D253G30.DA 2530mm - 7101lm	White
●	N10D253G02.DA 2530mm - 7101lm	Anodized Grey
●	N10D253G14.DA 2530mm - 7101lm	Black
●	N10D303G30.DA 3095mm - 8679lm	White
●	N10D303G02.DA 3095mm - 8679lm	Anodized Grey
●	N10D303G14.DA 3095mm - 8679lm	Black
●	N10DFC3G30.DA Flat Corner - 3156lm	White
●	N10DFC3G02.DA Flat Corner - 3156lm	Anodized Grey
●	N10DFC3G14.DA Flat Corner - 3156lm	Black
●	N10DEM3G30.DA Emergency - 3945lm	White
●	N10DEM3G02.DA Emergency - 3945lm	Anodized Grey
●	N10DEM3G14.DA Emergency - 3945lm	Black

In-Finity 100 Suspension Down 3000K General Lighting Dali . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Down 3000K General Lighting Dali designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D053G30.DA 565mm - 1578lm **White**
- N10D053G02.DA 565mm - 1578lm **Anodized Grey**
- N10D053G14.DA 565mm - 1578lm **Black**
- N10D083G30.DA 845mm - 2367lm **White**
- N10D083G02.DA 845mm - 2367lm **Anodized Grey**
- N10D083G14.DA 845mm - 2367lm **Black**
- N10D113G30.DA 1125mm - 3156lm **White**
- N10D113G02.DA 1125mm - 3156lm **Anodized Grey**
- N10D113G14.DA 1125mm - 3156lm **Black**
- N10D143G30.DA 1405mm - 3945lm **White**
- N10D143G02.DA 1405mm - 3945lm **Anodized Grey**
- N10D143G14.DA 1405mm - 3945lm **Black**
- N10D163G30.DA 1690mm - 4734lm **White**
- N10D163G02.DA 1690mm - 4734lm **Anodized Grey**
- N10D163G14.DA 1690mm - 4734lm **Black**
- N10D193G30.DA 1970mm - 5523lm **White**
- N10D193G02.DA 1970mm - 5523lm **Anodized Grey**
- N10D193G14.DA 1970mm - 5523lm **Black**
- N10D253G30.DA 2530mm - 7101lm **White**
- N10D253G02.DA 2530mm - 7101lm **Anodized Grey**
- N10D253G14.DA 2530mm - 7101lm **Black**
- N10D303G30.DA 3095mm - 8679lm **White**
- N10D303G02.DA 3095mm - 8679lm **Anodized Grey**
- N10D303G14.DA 3095mm - 8679lm **Black**
- N10DFC3G30.DA Flat Corner - 3156lm **White**
- N10DFC3G02.DA Flat Corner - 3156lm **Anodized Grey**
- N10DFC3G14.DA Flat Corner - 3156lm **Black**
- N10DEM3G30.DA Emergency - 3945lm **White**
- N10DEM3G02.DA Emergency - 3945lm **Anodized Grey**
- N10DEM3G14.DA Emergency - 3945lm **Black**

In-Finity 100 Suspension Down 3000K General Lighting Dali . Accessories

Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-Finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 100 Suspension Down 3000K General Lighting Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Suspension Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D053G30.DA 565mm - 1578lm **White**
- N10D053G02.DA 565mm - 1578lm **Anodized Grey**
- N10D053G14.DA 565mm - 1578lm **Black**
- N10D083G30.DA 845mm - 2367lm **White**
- N10D083G02.DA 845mm - 2367lm **Anodized Grey**
- N10D083G14.DA 845mm - 2367lm **Black**
- N10D113G30.DA 1125mm - 3156lm **White**
- N10D113G02.DA 1125mm - 3156lm **Anodized Grey**
- N10D113G14.DA 1125mm - 3156lm **Black**
- N10D143G30.DA 1405mm - 3945lm **White**
- N10D143G02.DA 1405mm - 3945lm **Anodized Grey**
- N10D143G14.DA 1405mm - 3945lm **Black**
- N10D163G30.DA 1690mm - 4734lm **White**
- N10D163G02.DA 1690mm - 4734lm **Anodized Grey**
- N10D163G14.DA 1690mm - 4734lm **Black**
- N10D193G30.DA 1970mm - 5523lm **White**
- N10D193G02.DA 1970mm - 5523lm **Anodized Grey**
- N10D193G14.DA 1970mm - 5523lm **Black**
- N10D253G30.DA 2530mm - 7101lm **White**
- N10D253G02.DA 2530mm - 7101lm **Anodized Grey**
- N10D253G14.DA 2530mm - 7101lm **Black**
- N10D303G30.DA 3095mm - 8679lm **White**
- N10D303G02.DA 3095mm - 8679lm **Anodized Grey**
- N10D303G14.DA 3095mm - 8679lm **Black**
- N10DFC3G30.DA Flat Corner - 3156lm **White**
- N10DFC3G02.DA Flat Corner - 3156lm **Anodized Grey**
- N10DFC3G14.DA Flat Corner - 3156lm **Black**
- N10DEM3G30.DA Emergency - 3945lm **White**
- N10DEM3G02.DA Emergency - 3945lm **Anodized Grey**
- N10DEM3G14.DA Emergency - 3945lm **Black**