


## IN-FINITY 100 SUSPENSION DOWN 4000K GENERAL LIGHTING DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant
<b>Lamps description</b>	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



### In-Finity 100 Suspension Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	109°

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



●	N10D054G30.DA 565mm - 1555lm	White
●	N10D054G02.DA 565mm - 1555lm	Anodized Grey
●	N10D054G14.DA 565mm - 1555lm	Black
●	N10D084G30.DA 845mm - 2333lm	White
●	N10D084G02.DA 845mm - 2333lm	Anodized Grey
●	N10D084G14.DA 845mm - 2333lm	Black
●	N10D114G30.DA 1125mm - 3111lm	White
●	N10D114G02.DA 1125mm - 3111lm	Anodized Grey
●	N10D114G14.DA 1125mm - 3111lm	Black
●	N10D144G30.DA 1405mm - 3889lm	White
●	N10D144G02.DA 1405mm - 3889lm	Anodized Grey
●	N10D144G14.DA 1405mm - 3889lm	Black
●	N10D164G30.DA 1690mm - 4667lm	White
●	N10D164G02.DA 1690mm - 4667lm	Anodized Grey
●	N10D164G14.DA 1690mm - 4667lm	Black
●	N10D194G30.DA 1970mm - 5445lm	White
●	N10D194G02.DA 1970mm - 5445lm	Anodized Grey
●	N10D194G14.DA 1970mm - 5445lm	Black
●	N10D254G30.DA 2530mm - 7001lm	White
●	N10D254G02.DA 2530mm - 7001lm	Anodized Grey
●	N10D254G14.DA 2530mm - 7001lm	Black
●	N10D304G30.DA 3095mm - 8557lm	White
●	N10D304G02.DA 3095mm - 8557lm	Anodized Grey
●	N10D304G14.DA 3095mm - 8557lm	Black
●	N10DFC4G30.DA Flat Corner - 3111lm	White
●	N10DFC4G02.DA Flat Corner - 3111lm	Anodized Grey
●	N10DFC4G14.DA Flat Corner - 3111lm	Black
●	N10DEM4G30.DA Emergency - 3889lm	White
●	N10DEM4G02.DA Emergency - 3889lm	Anodized Grey
●	N10DEM4G14.DA Emergency - 3889lm	Black

## In-Finity 100 Suspension Down 4000K General Lighting Dali . Accessories

### Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

#### Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 100 Suspension Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D054G30.DA 565mm - 1555lm White
- N10D054G02.DA 565mm - 1555lm Anodized Grey
- N10D054G14.DA 565mm - 1555lm Black
- N10D084G30.DA 845mm - 2333lm White
- N10D084G02.DA 845mm - 2333lm Anodized Grey
- N10D084G14.DA 845mm - 2333lm Black
- N10D114G30.DA 1125mm - 3111lm White
- N10D114G02.DA 1125mm - 3111lm Anodized Grey
- N10D114G14.DA 1125mm - 3111lm Black
- N10D144G30.DA 1405mm - 3889lm White
- N10D144G02.DA 1405mm - 3889lm Anodized Grey
- N10D144G14.DA 1405mm - 3889lm Black
- N10D164G30.DA 1690mm - 4667lm White
- N10D164G02.DA 1690mm - 4667lm Anodized Grey
- N10D164G14.DA 1690mm - 4667lm Black
- N10D194G30.DA 1970mm - 5445lm White
- N10D194G02.DA 1970mm - 5445lm Anodized Grey
- N10D194G14.DA 1970mm - 5445lm Black
- N10D254G30.DA 2530mm - 7001lm White
- N10D254G02.DA 2530mm - 7001lm Anodized Grey
- N10D254G14.DA 2530mm - 7001lm Black
- N10D304G30.DA 3095mm - 8557lm White
- N10D304G02.DA 3095mm - 8557lm Anodized Grey
- N10D304G14.DA 3095mm - 8557lm Black
- N10DFC4G30.DA Flat Corner - 3111lm White
- N10DFC4G02.DA Flat Corner - 3111lm Anodized Grey
- N10DFC4G14.DA Flat Corner - 3111lm Black
- N10DEM4G30.DA Emergency - 3889lm White
- N10DEM4G02.DA Emergency - 3889lm Anodized Grey
- N10DEM4G14.DA Emergency - 3889lm Black

## In-Finity 100 Suspension Down 4000K General Lighting Dali . Accessories

### Electrical



08.0031.00.DA

#### Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 100 Suspension Down 4000K General Lighting Dali . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



## In-Finity 100 Suspension Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D054G30.DA 565mm - 1555lm White
- N10D054G02.DA 565mm - 1555lm Anodized Grey
- N10D054G14.DA 565mm - 1555lm Black
- N10D084G30.DA 845mm - 2333lm White
- N10D084G02.DA 845mm - 2333lm Anodized Grey
- N10D084G14.DA 845mm - 2333lm Black
- N10D114G30.DA 1125mm - 3111lm White
- N10D114G02.DA 1125mm - 3111lm Anodized Grey
- N10D114G14.DA 1125mm - 3111lm Black
- N10D144G30.DA 1405mm - 3889lm White
- N10D144G02.DA 1405mm - 3889lm Anodized Grey
- N10D144G14.DA 1405mm - 3889lm Black
- N10D164G30.DA 1690mm - 4667lm White
- N10D164G02.DA 1690mm - 4667lm Anodized Grey
- N10D164G14.DA 1690mm - 4667lm Black
- N10D194G30.DA 1970mm - 5445lm White
- N10D194G02.DA 1970mm - 5445lm Anodized Grey
- N10D194G14.DA 1970mm - 5445lm Black
- N10D254G30.DA 2530mm - 7001lm White
- N10D254G02.DA 2530mm - 7001lm Anodized Grey
- N10D254G14.DA 2530mm - 7001lm Black
- N10D304G30.DA 3095mm - 8557lm White
- N10D304G02.DA 3095mm - 8557lm Anodized Grey
- N10D304G14.DA 3095mm - 8557lm Black
- N10DFC4G30.DA Flat Corner - 3111lm White
- N10DFC4G02.DA Flat Corner - 3111lm Anodized Grey
- N10DFC4G14.DA Flat Corner - 3111lm Black
- N10DEM4G30.DA Emergency - 3889lm White
- N10DEM4G02.DA Emergency - 3889lm Anodized Grey
- N10DEM4G14.DA Emergency - 3889lm Black