


IN-FINITY 100 SUSPENSION DOWN 4000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	77°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N10D054U30.DA 565mm - 1580lm **White**
- N10D054U02.DA 565mm - 1580lm **Anodized Grey**
- N10D054U14.DA 565mm - 1580lm **Black**
- N10D084U30.DA 845mm - 2371lm **White**
- N10D084U02.DA 845mm - 2371lm **Anodized Grey**
- N10D084U14.DA 845mm - 2371lm **Black**
- N10D114U30.DA 1125mm - 3161lm **White**
- N10D114U02.DA 1125mm - 3161lm **Anodized Grey**
- N10D114U14.DA 1125mm - 3161lm **Black**
- N10D144U30.DA 1405mm - 3952lm **White**
- N10D144U02.DA 1405mm - 3952lm **Anodized Grey**
- N10D144U14.DA 1405mm - 3952lm **Black**
- N10D164U30.DA 1690mm - 4742lm **White**
- N10D164U02.DA 1690mm - 4742lm **Anodized Grey**
- N10D164U14.DA 1690mm - 4742lm **Black**
- N10D194U30.DA 1970mm - 5533lm **White**
- N10D194U02.DA 1970mm - 5533lm **Anodized Grey**
- N10D194U14.DA 1970mm - 5533lm **Black**
- N10D254U30.DA 2530mm - 7114lm **White**
- N10D254U02.DA 2530mm - 7114lm **Anodized Grey**
- N10D254U14.DA 2530mm - 7114lm **Black**
- N10D304U30.DA 3095mm - 8695lm **White**
- N10D304U02.DA 3095mm - 8695lm **Anodized Grey**
- N10D304U14.DA 3095mm - 8695lm **Black**
- N10DFC4U30.DA Flat Corner - 3161lm **White**
- N10DFC4U02.DA Flat Corner - 3161lm **Anodized Grey**
- N10DFC4U14.DA Flat Corner - 3161lm **Black**
- N10DEM4U30.DA Emergency - 3952lm **White**
- N10DEM4U02.DA Emergency - 3952lm **Anodized Grey**
- N10DEM4U14.DA Emergency - 3952lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N10D054U30.DA 565mm - 1580lm **White**
- N10D054U02.DA 565mm - 1580lm **Anodized Grey**
- N10D054U14.DA 565mm - 1580lm **Black**
- N10D084U30.DA 845mm - 2371lm **White**
- N10D084U02.DA 845mm - 2371lm **Anodized Grey**
- N10D084U14.DA 845mm - 2371lm **Black**
- N10D114U30.DA 1125mm - 3161lm **White**
- N10D114U02.DA 1125mm - 3161lm **Anodized Grey**
- N10D114U14.DA 1125mm - 3161lm **Black**
- N10D144U30.DA 1405mm - 3952lm **White**
- N10D144U02.DA 1405mm - 3952lm **Anodized Grey**
- N10D144U14.DA 1405mm - 3952lm **Black**
- N10D164U30.DA 1690mm - 4742lm **White**
- N10D164U02.DA 1690mm - 4742lm **Anodized Grey**
- N10D164U14.DA 1690mm - 4742lm **Black**
- N10D194U30.DA 1970mm - 5533lm **White**
- N10D194U02.DA 1970mm - 5533lm **Anodized Grey**
- N10D194U14.DA 1970mm - 5533lm **Black**
- N10D254U30.DA 2530mm - 7114lm **White**
- N10D254U02.DA 2530mm - 7114lm **Anodized Grey**
- N10D254U14.DA 2530mm - 7114lm **Black**
- N10D304U30.DA 3095mm - 8695lm **White**
- N10D304U02.DA 3095mm - 8695lm **Anodized Grey**
- N10D304U14.DA 3095mm - 8695lm **Black**
- N10DFC4U30.DA Flat Corner - 3161lm **White**
- N10DFC4U02.DA Flat Corner - 3161lm **Anodized Grey**
- N10DFC4U14.DA Flat Corner - 3161lm **Black**
- N10DEM4U30.DA Emergency - 3952lm **White**
- N10DEM4U02.DA Emergency - 3952lm **Anodized Grey**
- N10DEM4U14.DA Emergency - 3952lm **Black**

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Accessories


Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

In-Finity 100 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10D054U30.DA 565mm - 1580lm **White**
- N10D054U02.DA 565mm - 1580lm **Anodized Grey**
- N10D054U14.DA 565mm - 1580lm **Black**
- N10D084U30.DA 845mm - 2371lm **White**
- N10D084U02.DA 845mm - 2371lm **Anodized Grey**
- N10D084U14.DA 845mm - 2371lm **Black**
- N10D114U30.DA 1125mm - 3161lm **White**
- N10D114U02.DA 1125mm - 3161lm **Anodized Grey**
- N10D114U14.DA 1125mm - 3161lm **Black**
- N10D144U30.DA 1405mm - 3952lm **White**
- N10D144U02.DA 1405mm - 3952lm **Anodized Grey**
- N10D144U14.DA 1405mm - 3952lm **Black**
- N10D164U30.DA 1690mm - 4742lm **White**
- N10D164U02.DA 1690mm - 4742lm **Anodized Grey**
- N10D164U14.DA 1690mm - 4742lm **Black**
- N10D194U30.DA 1970mm - 5533lm **White**
- N10D194U02.DA 1970mm - 5533lm **Anodized Grey**
- N10D194U14.DA 1970mm - 5533lm **Black**
- N10D254U30.DA 2530mm - 7114lm **White**
- N10D254U02.DA 2530mm - 7114lm **Anodized Grey**
- N10D254U14.DA 2530mm - 7114lm **Black**
- N10D304U30.DA 3095mm - 8695lm **White**
- N10D304U02.DA 3095mm - 8695lm **Anodized Grey**
- N10D304U14.DA 3095mm - 8695lm **Black**
- N10DFC4U30.DA Flat Corner - 3161lm **White**
- N10DFC4U02.DA Flat Corner - 3161lm **Anodized Grey**
- N10DFC4U14.DA Flat Corner - 3161lm **Black**
- N10DEM4U30.DA Emergency - 3952lm **White**
- N10DEM4U02.DA Emergency - 3952lm **Anodized Grey**
- N10DEM4U14.DA Emergency - 3952lm **Black**