


## IN-FINITY 100 RECESSED NO TRIM 3000K MICRO-PRISMATIC DIFFUSER DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Recessed No Trim
<b>Lamps description</b>	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



### In-Finity 100 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	77°



### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I



### PHYSICAL

<b>Recessed depth (mm)</b>	135
<b>Construction material</b>	Aluminium

- N10N053U30.DA 565mm - 1607lm White
- N10N083U30.DA 845mm - 2410lm White
- N10N113U30.DA 1125mm - 3214lm White
- N10N143U30.DA 1405mm - 4017lm White
- N10N163U30.DA 1690mm - 4821lm White
- N10N193U30.DA 1970mm - 5624lm White
- N10N253U30.DA 2530mm - 7231lm White
- N10N303U30.DA 3095mm - 8838lm White
- N10NFC3U30.DA Flat Corner - White  
3214lm
- N10NDC3U30.DA Dihedral Corner - White  
3214lm
- N10NEM3U30.DA Emergency - White  
4017lm



### CERTIFICATIONS



## In-Finity 100 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali . Accessories


### Structural



08.9054.40

#### Metal cover. Recessed No Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.



### In-Finity 100 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## In-Finity 100 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali . Lamps



#### Top LED

#### Lamp category:

LED



#### Socket:

Special base

#### Lamp type:

Top LED

- N10N053U30.DA 565mm - 1607lm White
- N10N083U30.DA 845mm - 2410lm White
- N10N113U30.DA 1125mm - 3214lm White
- N10N143U30.DA 1405mm - 4017lm White
- N10N163U30.DA 1690mm - 4821lm White
- N10N193U30.DA 1970mm - 5624lm White
- N10N253U30.DA 2530mm - 7231lm White
- N10N303U30.DA 3095mm - 8838lm White
- N10NFC3U30.DA Flat Corner - White 3214lm
- N10NDC3U30.DA Dihedral Corner - White 3214lm
- N10NEM3U30.DA Emergency - White 4017lm



### CERTIFICATIONS

