


IN-FINITY 100 RECESSED NO TRIM 4000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Recessed No Trim
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Recessed No Trim 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	77°



ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I



PHYSICAL

Recessed depth (mm)	135
Construction material	Aluminium

- N10N054U30.DA 565mm - 1580lm White
- N10N084U30.DA 845mm - 2371lm White
- N10N114U30.DA 1125mm - 3161lm White
- N10N144U30.DA 1405mm - 3952lm White
- N10N164U30.DA 1690mm - 4742lm White
- N10N194U30.DA 1970mm - 5533lm White
- N10N254U30.DA 2530mm - 7114lm White
- N10N304U30.DA 3095mm - 8695lm White
- N10NFC4U30.DA Flat Corner - White
3161lm
- N10NDC4U30.DA Dihedral Corner - White
3161lm
- N10NEM4U30.DA Emergency - White
3952lm



CERTIFICATIONS



In-Finity 100 Recessed No Trim 4000K Micro-Prismatic Diffuser Dali . Accessories


Structural



08.9054.40

Metal cover. Recessed No Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Recessed No Trim 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

In-Finity 100 Recessed No Trim 4000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:

LED



Socket:

Special base

Lamp type:

Top LED

- N10N054U30.DA 565mm - 1580lm White
- N10N084U30.DA 845mm - 2371lm White
- N10N114U30.DA 1125mm - 3161lm White
- N10N144U30.DA 1405mm - 3952lm White
- N10N164U30.DA 1690mm - 4742lm White
- N10N194U30.DA 1970mm - 5533lm White
- N10N254U30.DA 2530mm - 7114lm White
- N10N304U30.DA 3095mm - 8695lm White
- N10NFC4U30.DA Flat Corner - White
3161lm
- N10NDC4U30.DA Dihedral Corner - White
3161lm
- N10NEM4U30.DA Emergency - White
3952lm



CERTIFICATIONS

