


IN-FINITY 100 SURFACE 3000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Surface
Lamps description	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Surface 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N10S053G30.DA 565mm - 1578lm White
- N10S053G02.DA 565mm - 1578lm Anodized Grey
- N10S053G14.DA 565mm - 1578lm Black
- N10S083G30.DA 845mm - 2367lm White
- N10S083G02.DA 845mm - 2367lm Anodized Grey
- N10S083G14.DA 845mm - 2367lm Black
- N10S113G30.DA 1125mm - 3156lm White
- N10S113G02.DA 1125mm - 3156lm Anodized Grey
- N10S113G14.DA 1125mm - 3156lm Black
- N10S143G30.DA 1405mm - 3945lm White
- N10S143G02.DA 1405mm - 3945lm Anodized Grey
- N10S143G14.DA 1405mm - 3945lm Black
- N10S163G30.DA 1690mm - 4734lm White
- N10S163G02.DA 1690mm - 4734lm Anodized Grey
- N10S163G14.DA 1690mm - 4734lm Black
- N10S193G30.DA 1970mm - 5523lm White
- N10S193G02.DA 1970mm - 5523lm Anodized Grey
- N10S193G14.DA 1970mm - 5523lm Black
- N10S253G30.DA 2530mm - 7101lm White
- N10S253G02.DA 2530mm - 7101lm Anodized Grey
- N10S253G14.DA 2530mm - 7101lm Black
- N10S303G30.DA 3095mm - 8679lm White
- N10S303G02.DA 3095mm - 8679lm Anodized Grey
- N10S303G14.DA 3095mm - 8679lm Black
- N10SFC3G30.DA Flat Corner - 3156lm White
- N10SFC3G02.DA Flat Corner - 3156lm Anodized Grey
- N10SFC3G14.DA Flat Corner - 3156lm Black
- N10SDC3G30.DA Dihedral Corner - 3156lm White
- N10SDC3G02.DA Dihedral Corner - 3156lm Anodized Grey
- N10SDC3G14.DA Dihedral Corner - 3156lm Black
- N10SEM3G30.DA Emergency - 3945lm White
- N10SEM3G02.DA Emergency - 3945lm Anodized Grey
- N10SEM3G14.DA Emergency - 3945lm Black

In-Finity 100 Surface 3000K General Lighting Dali . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 100 Surface 3000K General Lighting Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Surface 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N10S053G30.DA 565mm - 1578lm White
- N10S053G02.DA 565mm - 1578lm Anodized Grey
- N10S053G14.DA 565mm - 1578lm Black
- N10S083G30.DA 845mm - 2367lm White
- N10S083G02.DA 845mm - 2367lm Anodized Grey
- N10S083G14.DA 845mm - 2367lm Black
- N10S113G30.DA 1125mm - 3156lm White
- N10S113G02.DA 1125mm - 3156lm Anodized Grey
- N10S113G14.DA 1125mm - 3156lm Black
- N10S143G30.DA 1405mm - 3945lm White
- N10S143G02.DA 1405mm - 3945lm Anodized Grey
- N10S143G14.DA 1405mm - 3945lm Black
- N10S163G30.DA 1690mm - 4734lm White
- N10S163G02.DA 1690mm - 4734lm Anodized Grey
- N10S163G14.DA 1690mm - 4734lm Black
- N10S193G30.DA 1970mm - 5523lm White
- N10S193G02.DA 1970mm - 5523lm Anodized Grey
- N10S193G14.DA 1970mm - 5523lm Black
- N10S253G30.DA 2530mm - 7101lm White
- N10S253G02.DA 2530mm - 7101lm Anodized Grey
- N10S253G14.DA 2530mm - 7101lm Black
- N10S303G30.DA 3095mm - 8679lm White
- N10S303G02.DA 3095mm - 8679lm Anodized Grey
- N10S303G14.DA 3095mm - 8679lm Black
- N10SFC3G30.DA Flat Corner - 3156lm White
- N10SFC3G02.DA Flat Corner - 3156lm Anodized Grey
- N10SFC3G14.DA Flat Corner - 3156lm Black
- N10SDC3G30.DA Dihedral Corner - 3156lm White
- N10SDC3G02.DA Dihedral Corner - 3156lm Anodized Grey
- N10SDC3G14.DA Dihedral Corner - 3156lm Black
- N10SEM3G30.DA Emergency - 3945lm White
- N10SEM3G02.DA Emergency - 3945lm Anodized Grey
- N10SEM3G14.DA Emergency - 3945lm Black