


IN-FINITY 100 SURFACE 3000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Surface
Lamps description	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	77°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N10S053U30 565mm - 1607lm White
- N10S053U02 565mm - 1607lm Anodized Grey
- N10S053U14 565mm - 1607lm Black
- N10S083U30 845mm - 2410lm White
- N10S083U02 845mm - 2410lm Anodized Grey
- N10S083U14 845mm - 2410lm Black
- N10S113U30 1125mm - 3214lm White
- N10S113U02 1125mm - 3214lm Anodized Grey
- N10S113U14 1125mm - 3214lm Black
- N10S143U30 1405mm - 4017lm White
- N10S143U02 1405mm - 4017lm Anodized Grey
- N10S143U14 1405mm - 4017lm Black
- N10S163U30 1690mm - 4821lm White
- N10S163U02 1690mm - 4821lm Anodized Grey
- N10S163U14 1690mm - 4821lm Black
- N10S193U30 1970mm - 5624lm White
- N10S193U02 1970mm - 5624lm Anodized Grey
- N10S193U14 1970mm - 5624lm Black
- N10S253U30 2530mm - 7231lm White
- N10S253U02 2530mm - 7231lm Anodized Grey
- N10S253U14 2530mm - 7231lm Black
- N10S303U30 3095mm - 8838lm White
- N10S303U02 3095mm - 8838lm Anodized Grey
- N10S303U14 3095mm - 8838lm Black
- N10SFC3U30 Flat Corner - 3214lm White
- N10SFC3U02 Flat Corner - 3214lm Anodized Grey
- N10SFC3U14 Flat Corner - 3214lm Black
- N10SDC3U30 Dihedral Corner - 3214lm White
- N10SDC3U02 Dihedral Corner - 3214lm Anodized Grey
- N10SDC3U14 Dihedral Corner - 3214lm Black
- N10SEM3U30 Emergency - 4017lm White
- N10SEM3U02 Emergency - 4017lm Anodized Grey
- N10SEM3U14 Emergency - 4017lm Black

In-Finity 100 Surface 3000K Micro-Prismatic Diffuser . Accessories


Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

In-Finity 100 Surface 3000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10S053U30 565mm - 1607lm White
- N10S053U02 565mm - 1607lm Anodized Grey
- N10S053U14 565mm - 1607lm Black
- N10S083U30 845mm - 2410lm White
- N10S083U02 845mm - 2410lm Anodized Grey
- N10S083U14 845mm - 2410lm Black
- N10S113U30 1125mm - 3214lm White
- N10S113U02 1125mm - 3214lm Anodized Grey
- N10S113U14 1125mm - 3214lm Black
- N10S143U30 1405mm - 4017lm White
- N10S143U02 1405mm - 4017lm Anodized Grey
- N10S143U14 1405mm - 4017lm Black
- N10S163U30 1690mm - 4821lm White
- N10S163U02 1690mm - 4821lm Anodized Grey
- N10S163U14 1690mm - 4821lm Black
- N10S193U30 1970mm - 5624lm White
- N10S193U02 1970mm - 5624lm Anodized Grey
- N10S193U14 1970mm - 5624lm Black
- N10S253U30 2530mm - 7231lm White
- N10S253U02 2530mm - 7231lm Anodized Grey
- N10S253U14 2530mm - 7231lm Black
- N10S303U30 3095mm - 8838lm White
- N10S303U02 3095mm - 8838lm Anodized Grey
- N10S303U14 3095mm - 8838lm Black
- N10SFC3U30 Flat Corner - 3214lm White
- N10SFC3U02 Flat Corner - 3214lm Anodized Grey
- N10SFC3U14 Flat Corner - 3214lm Black
- N10SDC3U30 Dihedral Corner - 3214lm White
- N10SDC3U02 Dihedral Corner - 3214lm Anodized Grey
- N10SDC3U14 Dihedral Corner - 3214lm Black
- N10SEM3U30 Emergency - 4017lm White
- N10SEM3U02 Emergency - 4017lm Anodized Grey
- N10SEM3U14 Emergency - 4017lm Black