


IN-FINITY 100 SURFACE 3000K MICRO-PRISMATIC DIFFUSER DALI

| | |
|--------------------------------|---|
| Number of heads | 1 |
| Mounting | Surface |
| Lamps description | Top LED 34,1W/m 3915 lm/m 3000K CRI 80 |
| Luminaire luminous flux | See reference number |
| Voltage (V) | 220/240 |
| Environment | Indoor |
| Notes | Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps. |



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali
designed by FLOS Architectural

OPTICAL

| | |
|------------------------------------|-----------|
| Aiming | Fixed |
| Light distribution symmetry | Symmetric |
| Beam angle | 77° |

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

ELECTRICAL

| | |
|---------------------------------|--------------------------|
| Transformer availability | Included |
| Transformer mounting | Integral |
| Transformer type | Electronic dimmable dali |
| Emergency | Without |
| Insulation class | Class I |

- N10S053U30.DA 565mm - 1607lm White
- N10S053U02.DA 565mm - 1607lm Anodized Grey
- N10S053U14.DA 565mm - 1607lm Black
- N10S083U30.DA 845mm - 2410lm White
- N10S083U02.DA 845mm - 2410lm Anodized Grey
- N10S083U14.DA 845mm - 2410lm Black
- N10S113U30.DA 1125mm - 3214lm White
- N10S113U02.DA 1125mm - 3214lm Anodized Grey
- N10S113U14.DA 1125mm - 3214lm Black
- N10S143U30.DA 1405mm - 4017lm White
- N10S143U02.DA 1405mm - 4017lm Anodized Grey
- N10S143U14.DA 1405mm - 4017lm Black
- N10S163U30.DA 1690mm - 4821lm White
- N10S163U02.DA 1690mm - 4821lm Anodized Grey
- N10S163U14.DA 1690mm - 4821lm Black
- N10S193U30.DA 1970mm - 5624lm White
- N10S193U02.DA 1970mm - 5624lm Anodized Grey
- N10S193U14.DA 1970mm - 5624lm Black
- N10S253U30.DA 2530mm - 7231lm White
- N10S253U02.DA 2530mm - 7231lm Anodized Grey
- N10S253U14.DA 2530mm - 7231lm Black
- N10S303U30.DA 3095mm - 8838lm White
- N10S303U02.DA 3095mm - 8838lm Anodized Grey
- N10S303U14.DA 3095mm - 8838lm Black
- N10SFC3U30.DA Flat Corner - 3214lm White
- N10SFC3U02.DA Flat Corner - 3214lm Anodized Grey
- N10SFC3U14.DA Flat Corner - 3214lm Black
- N10SDC3U30.DA Dihedral Corner - 3214lm White
- N10SDC3U02.DA Dihedral Corner - 3214lm Anodized Grey
- N10SDC3U14.DA Dihedral Corner - 3214lm Black
- N10SEM3U30.DA Emergency - 4017lm White
- N10SEM3U02.DA Emergency - 4017lm Anodized Grey
- N10SEM3U14.DA Emergency - 4017lm Black

PHYSICAL

| | |
|------------------------------|-----------|
| Construction material | Aluminium |
|------------------------------|-----------|



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Surface 3000K Micro-Prismatic Diffuser Dali designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N10S053U30.DA 565mm - 1607lm White
- N10S053U02.DA 565mm - 1607lm Anodized Grey
- N10S053U14.DA 565mm - 1607lm Black
- N10S083U30.DA 845mm - 2410lm White
- N10S083U02.DA 845mm - 2410lm Anodized Grey
- N10S083U14.DA 845mm - 2410lm Black
- N10S113U30.DA 1125mm - 3214lm White
- N10S113U02.DA 1125mm - 3214lm Anodized Grey
- N10S113U14.DA 1125mm - 3214lm Black
- N10S143U30.DA 1405mm - 4017lm White
- N10S143U02.DA 1405mm - 4017lm Anodized Grey
- N10S143U14.DA 1405mm - 4017lm Black
- N10S163U30.DA 1690mm - 4821lm White
- N10S163U02.DA 1690mm - 4821lm Anodized Grey
- N10S163U14.DA 1690mm - 4821lm Black
- N10S193U30.DA 1970mm - 5624lm White
- N10S193U02.DA 1970mm - 5624lm Anodized Grey
- N10S193U14.DA 1970mm - 5624lm Black
- N10S253U30.DA 2530mm - 7231lm White
- N10S253U02.DA 2530mm - 7231lm Anodized Grey
- N10S253U14.DA 2530mm - 7231lm Black
- N10S303U30.DA 3095mm - 8838lm White
- N10S303U02.DA 3095mm - 8838lm Anodized Grey
- N10S303U14.DA 3095mm - 8838lm Black
- N10SFC3U30.DA Flat Corner - 3214lm White
- N10SFC3U02.DA Flat Corner - 3214lm Anodized Grey
- N10SFC3U14.DA Flat Corner - 3214lm Black
- N10SDC3U30.DA Dihedral Corner - 3214lm White
- N10SDC3U02.DA Dihedral Corner - 3214lm Anodized Grey
- N10SDC3U14.DA Dihedral Corner - 3214lm Black
- N10SEM3U30.DA Emergency - 4017lm White
- N10SEM3U02.DA Emergency - 4017lm Anodized Grey
- N10SEM3U14.DA Emergency - 4017lm Black