


IN-FINITY 100 SURFACE 4000K GENERAL LIGHTING

Number of heads	1
Mounting	Surface
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Surface 4000K General Lighting

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N10S054G30 565mm - 1555lm White
- N10S054G02 565mm - 1555lm Anodized Grey
- N10S054G14 565mm - 1555lm Black
- N10S084G30 845mm - 2333lm White
- N10S084G02 845mm - 2333lm Anodized Grey
- N10S084G14 845mm - 2333lm Black
- N10S114G30 1125mm - 3111lm White
- N10S114G02 1125mm - 3111lm Anodized Grey
- N10S114G14 1125mm - 3111lm Black
- N10S144G30 1405mm - 3889lm White
- N10S144G02 1405mm - 3889lm Anodized Grey
- N10S144G14 1405mm - 3889lm Black
- N10S164G30 1690mm - 4667lm White
- N10S164G02 1690mm - 4667lm Anodized Grey
- N10S164G14 1690mm - 4667lm Black
- N10S194G30 1970mm - 5445lm White
- N10S194G02 1970mm - 5445lm Anodized Grey
- N10S194G14 1970mm - 5445lm Black
- N10S254G30 2530mm - 7001lm White
- N10S254G02 2530mm - 7001lm Anodized Grey
- N10S254G14 2530mm - 7001lm Black
- N10S304G30 3095mm - 8557lm White
- N10S304G02 3095mm - 8557lm Anodized Grey
- N10S304G14 3095mm - 8557lm Black
- N10SFC4G30 Flat Corner - 3111lm White
- N10SFC4G02 Flat Corner - 3111lm Anodized Grey
- N10SFC4G14 Flat Corner - 3111lm Black
- N10SDC4G30 Dihedral Corner - 3111lm White
- N10SDC4G02 Dihedral Corner - 3111lm Anodized Grey
- N10SDC4G14 Dihedral Corner - 3111lm Black
- N10SEM4G30 Emergency - 3889lm White
- N10SEM4G02 Emergency - 3889lm Anodized Grey
- N10SEM4G14 Emergency - 3889lm Black

In-Finity 100 Surface 4000K General Lighting . Accessories

Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

Metal cover. Surface / Suspension Down. 100 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 100 Surface 4000K General Lighting . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Surface 4000K General Lighting

designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- NI0S054G30 565mm - 1555lm White
- NI0S054G02 565mm - 1555lm Anodized Grey
- NI0S054G14 565mm - 1555lm Black
- NI0S084G30 845mm - 2333lm White
- NI0S084G02 845mm - 2333lm Anodized Grey
- NI0S084G14 845mm - 2333lm Black
- NI0S114G30 1125mm - 3111lm White
- NI0S114G02 1125mm - 3111lm Anodized Grey
- NI0S114G14 1125mm - 3111lm Black
- NI0S144G30 1405mm - 3889lm White
- NI0S144G02 1405mm - 3889lm Anodized Grey
- NI0S144G14 1405mm - 3889lm Black
- NI0S164G30 1690mm - 4667lm White
- NI0S164G02 1690mm - 4667lm Anodized Grey
- NI0S164G14 1690mm - 4667lm Black
- NI0S194G30 1970mm - 5445lm White
- NI0S194G02 1970mm - 5445lm Anodized Grey
- NI0S194G14 1970mm - 5445lm Black
- NI0S254G30 2530mm - 7001lm White
- NI0S254G02 2530mm - 7001lm Anodized Grey
- NI0S254G14 2530mm - 7001lm Black
- NI0S304G30 3095mm - 8557lm White
- NI0S304G02 3095mm - 8557lm Anodized Grey
- NI0S304G14 3095mm - 8557lm Black
- NI0SFC4G30 Flat Corner - 3111lm White
- NI0SFC4G02 Flat Corner - 3111lm Anodized Grey
- NI0SFC4G14 Flat Corner - 3111lm Black
- NI0SDC4G30 Dihedral Corner - 3111lm White
- NI0SDC4G02 Dihedral Corner - 3111lm Anodized Grey
- NI0SDC4G14 Dihedral Corner - 3111lm Black
- NI0SEM4G30 Emergency - 3889lm White
- NI0SEM4G02 Emergency - 3889lm Anodized Grey
- NI0SEM4G14 Emergency - 3889lm Black