


## IN-FINITY 100 SURFACE 4000K MICRO-PRISMATIC DIFFUSER DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Surface
<b>Lamps description</b>	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 100 Surface 4000K Micro-Prismatic Diffuser Dali**  
designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	77°

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N10S054U30.DA 565mm - 1580lm White
- N10S054U02.DA 565mm - 1580lm Anodized Grey
- N10S054U14.DA 565mm - 1580lm Black
- N10S084U30.DA 845mm - 2371lm White
- N10S084U02.DA 845mm - 2371lm Anodized Grey
- N10S084U14.DA 845mm - 2371lm Black
- N10S114U30.DA 1125mm - 3161lm White
- N10S114U02.DA 1125mm - 3161lm Anodized Grey
- N10S114U14.DA 1125mm - 3161lm Black
- N10S144U30.DA 1405mm - 3952lm White
- N10S144U02.DA 1405mm - 3952lm Anodized Grey
- N10S144U14.DA 1405mm - 3952lm Black
- N10S164U30.DA 1690mm - 4742lm White
- N10S164U02.DA 1690mm - 4742lm Anodized Grey
- N10S164U14.DA 1690mm - 4742lm Black
- N10S194U30.DA 1970mm - 5533lm White
- N10S194U02.DA 1970mm - 5533lm Anodized Grey
- N10S194U14.DA 1970mm - 5533lm Black
- N10S254U30.DA 2530mm - 7114lm White
- N10S254U02.DA 2530mm - 7114lm Anodized Grey
- N10S254U14.DA 2530mm - 7114lm Black
- N10S304U30.DA 3095mm - 8695lm White
- N10S304U02.DA 3095mm - 8695lm Anodized Grey
- N10S304U14.DA 3095mm - 8695lm Black
- N10SFC4U30.DA Flat Corner - 3161lm White
- N10SFC4U02.DA Flat Corner - 3161lm Anodized Grey
- N10SFC4U14.DA Flat Corner - 3161lm Black
- N10SDC4U30.DA Dihedral Corner - 3161lm White
- N10SDC4U02.DA Dihedral Corner - 3161lm Anodized Grey
- N10SDC4U14.DA Dihedral Corner - 3161lm Black
- N10SEM4U30.DA Emergency - 3952lm White
- N10SEM4U02.DA Emergency - 3952lm Anodized Grey
- N10SEM4U14.DA Emergency - 3952lm Black

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 100 Surface 4000K Micro-Prismatic Diffuser Dali . Accessories

### Structural



- 08.9054.40
- 08.9054.02
- 08.9054.NS
- 08.9054.06

**Metal cover. Surface / Suspension Down. 100 mm**

Metal cover for the different profiles. 2 unit kit.

## In-Finity 100 Surface 4000K Micro-Prismatic Diffuser Dali . Lamps



**Top LED**

**Lamp category:**


LED

**Socket:**

Special base

**Lamp type:**

Top LED



**In-Finity 100 Surface 4000K Micro-Prismatic Diffuser Dali**  
designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N10S054U30.DA 565mm - 1580lm White
- N10S054U02.DA 565mm - 1580lm Anodized Grey
- N10S054U14.DA 565mm - 1580lm Black
- N10S084U30.DA 845mm - 2371lm White
- N10S084U02.DA 845mm - 2371lm Anodized Grey
- N10S084U14.DA 845mm - 2371lm Black
- N10S114U30.DA 1125mm - 3161lm White
- N10S114U02.DA 1125mm - 3161lm Anodized Grey
- N10S114U14.DA 1125mm - 3161lm Black
- N10S144U30.DA 1405mm - 3952lm White
- N10S144U02.DA 1405mm - 3952lm Anodized Grey
- N10S144U14.DA 1405mm - 3952lm Black
- N10S164U30.DA 1690mm - 4742lm White
- N10S164U02.DA 1690mm - 4742lm Anodized Grey
- N10S164U14.DA 1690mm - 4742lm Black
- N10S194U30.DA 1970mm - 5533lm White
- N10S194U02.DA 1970mm - 5533lm Anodized Grey
- N10S194U14.DA 1970mm - 5533lm Black
- N10S254U30.DA 2530mm - 7114lm White
- N10S254U02.DA 2530mm - 7114lm Anodized Grey
- N10S254U14.DA 2530mm - 7114lm Black
- N10S304U30.DA 3095mm - 8695lm White
- N10S304U02.DA 3095mm - 8695lm Anodized Grey
- N10S304U14.DA 3095mm - 8695lm Black
- N10SFC4U30.DA Flat Corner - 3161lm White
- N10SFC4U02.DA Flat Corner - 3161lm Anodized Grey
- N10SFC4U14.DA Flat Corner - 3161lm Black
- N10SDC4U30.DA Dihedral Corner - 3161lm White
- N10SDC4U02.DA Dihedral Corner - 3161lm Anodized Grey
- N10SDC4U14.DA Dihedral Corner - 3161lm Black
- N10SEM4U30.DA Emergency - 3952lm White
- N10SEM4U02.DA Emergency - 3952lm Anodized Grey
- N10SEM4U14.DA Emergency - 3952lm Black