


## IN-FINITY 100 RECESSED TRIM 3000K GENERAL LIGHTING

<b>Number of heads</b>	1
<b>Mounting</b>	Recessed Trim
<b>Lamps description</b>	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps



### In-Finity 100 Recessed Trim 3000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	109°

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Recessed depth (mm)</b>	135
<b>Construction material</b>	Aluminium



- NI0T053G30 565mm - 1578lm White
- NI0T053G02 565mm - 1578lm Anodized Grey
- NI0T053G14 565mm - 1578lm Black
- NI0T083G30 845mm - 2367lm White
- NI0T083G02 845mm - 2367lm Anodized Grey
- NI0T083G14 845mm - 2367lm Black
- NI0T113G30 1125mm - 3156lm White
- NI0T113G02 1125mm - 3156lm Anodized Grey
- NI0T113G14 1125mm - 3156lm Black
- NI0T143G30 1405mm - 3945lm White
- NI0T143G02 1405mm - 3945lm Anodized Grey
- NI0T143G14 1405mm - 3945lm Black
- NI0T163G30 1690mm - 4734lm White
- NI0T163G02 1690mm - 4734lm Anodized Grey
- NI0T163G14 1690mm - 4734lm Black
- NI0T193G30 1970mm - 5523lm White
- NI0T193G02 1970mm - 5523lm Anodized Grey
- NI0T193G14 1970mm - 5523lm Black
- NI0T253G30 2530mm - 7101lm White
- NI0T253G02 2530mm - 7101lm Anodized Grey
- NI0T253G14 2530mm - 7101lm Black
- NI0T303G30 3095mm - 8679lm White
- NI0T303G02 3095mm - 8679lm Anodized Grey
- NI0T303G14 3095mm - 8679lm Black
- NI0TFC3G30 Flat Corner - 3156lm White
- NI0TFC3G02 Flat Corner - 3156lm Anodized Grey
- NI0TFC3G14 Flat Corner - 3156lm Black
- NI0TDC3G30 Dihedral Corner - 3156lm White
- NI0TDC3G02 Dihedral Corner - 3156lm Anodized Grey
- NI0TDC3G14 Dihedral Corner - 3156lm Black
- NI0TEM3G30 Emergency - 3945lm White
- NI0TEM3G02 Emergency - 3945lm Anodized Grey
- NI0TEM3G14 Emergency - 3945lm Black

## In-Finity 100 Recessed Trim 3000K General Lighting . Accessories


### Structural



- 08.9055.40
- 08.9055.02
- 08.9055.NS

#### Metal cover. Recessed Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.



### In-Finity 100 Recessed Trim 3000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## In-Finity 100 Recessed Trim 3000K General Lighting . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED

- NI0T053G30 565mm - 1578lm White
- NI0T053G02 565mm - 1578lm Anodized Grey
- NI0T053G14 565mm - 1578lm Black
- NI0T083G30 845mm - 2367lm White
- NI0T083G02 845mm - 2367lm Anodized Grey
- NI0T083G14 845mm - 2367lm Black
- NI0T113G30 1125mm - 3156lm White
- NI0T113G02 1125mm - 3156lm Anodized Grey
- NI0T113G14 1125mm - 3156lm Black
- NI0T143G30 1405mm - 3945lm White
- NI0T143G02 1405mm - 3945lm Anodized Grey
- NI0T143G14 1405mm - 3945lm Black
- NI0T163G30 1690mm - 4734lm White
- NI0T163G02 1690mm - 4734lm Anodized Grey
- NI0T163G14 1690mm - 4734lm Black
- NI0T193G30 1970mm - 5523lm White
- NI0T193G02 1970mm - 5523lm Anodized Grey
- NI0T193G14 1970mm - 5523lm Black
- NI0T253G30 2530mm - 7101lm White
- NI0T253G02 2530mm - 7101lm Anodized Grey
- NI0T253G14 2530mm - 7101lm Black
- NI0T303G30 3095mm - 8679lm White
- NI0T303G02 3095mm - 8679lm Anodized Grey
- NI0T303G14 3095mm - 8679lm Black
- NI0TFC3G30 Flat Corner - 3156lm White
- NI0TFC3G02 Flat Corner - 3156lm Anodized Grey
- NI0TFC3G14 Flat Corner - 3156lm Black
- NI0TDC3G30 Dihedral Corner - 3156lm White
- NI0TDC3G02 Dihedral Corner - 3156lm Anodized Grey
- NI0TDC3G14 Dihedral Corner - 3156lm Black
- NI0TEM3G30 Emergency - 3945lm White
- NI0TEM3G02 Emergency - 3945lm Anodized Grey
- NI0TEM3G14 Emergency - 3945lm Black