


IN-FINITY 100 RECESSED TRIM 3000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Recessed Trim
Lamps description	Top LED 34,1W/m 3915 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Recessed Trim 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	77°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

PHYSICAL

Recessed depth (mm)	135
Construction material	Aluminium



- N10T053U30.DA 565mm - 1607lm White
- N10T053U02.DA 565mm - 1607lm Anodized Grey
- N10T053U14.DA 565mm - 1607lm Black
- N10T083U30.DA 845mm - 2410lm White
- N10T083U02.DA 845mm - 2410lm Anodized Grey
- N10T083U14.DA 845mm - 2410lm Black
- N10T113U30.DA 1125mm - 3214lm White
- N10T113U02.DA 1125mm - 3214lm Anodized Grey
- N10T113U14.DA 1125mm - 3214lm Black
- N10T143U30.DA 1405mm - 4017lm White
- N10T143U02.DA 1405mm - 4017lm Anodized Grey
- N10T143U14.DA 1405mm - 4017lm Black
- N10T163U30.DA 1690mm - 4821lm White
- N10T163U02.DA 1690mm - 4821lm Anodized Grey
- N10T163U14.DA 1690mm - 4821lm Black
- N10T193U30.DA 1970mm - 5624lm White
- N10T193U02.DA 1970mm - 5624lm Anodized Grey
- N10T193U14.DA 1970mm - 5624lm Black
- N10T253U30.DA 2530mm - 7231lm White
- N10T253U02.DA 2530mm - 7231lm Anodized Grey
- N10T253U14.DA 2530mm - 7231lm Black
- N10T303U30.DA 3095mm - 8838lm White
- N10T303U02.DA 3095mm - 8838lm Anodized Grey
- N10T303U14.DA 3095mm - 8838lm Black
- N10TFC3U30.DA Flat Corner - 3214lm White
- N10TFC3U02.DA Flat Corner - 3214lm Anodized Grey
- N10TFC3U14.DA Flat Corner - 3214lm Black
- N10TDC3U30.DA Dihedral Corner - 3214lm White
- N10TDC3U02.DA Dihedral Corner - 3214lm Anodized Grey
- N10TDC3U14.DA Dihedral Corner - 3214lm Black
- N10TEM3U30.DA Emergency - 4017lm White
- N10TEM3U02.DA Emergency - 4017lm Anodized Grey
- N10TEM3U14.DA Emergency - 4017lm Black

In-Finity 100 Recessed Trim 3000K Micro-Prismatic Diffuser Dali . Accessories


Structural



- 08.9055.40
- 08.9055.02
- 08.9055.NS

Metal cover. Recessed Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Recessed Trim 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

In-Finity 100 Recessed Trim 3000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10T053U30.DA 565mm - 1607lm White
- N10T053U02.DA 565mm - 1607lm Anodized Grey
- N10T053U14.DA 565mm - 1607lm Black
- N10T083U30.DA 845mm - 2410lm White
- N10T083U02.DA 845mm - 2410lm Anodized Grey
- N10T083U14.DA 845mm - 2410lm Black
- N10T113U30.DA 1125mm - 3214lm White
- N10T113U02.DA 1125mm - 3214lm Anodized Grey
- N10T113U14.DA 1125mm - 3214lm Black
- N10T143U30.DA 1405mm - 4017lm White
- N10T143U02.DA 1405mm - 4017lm Anodized Grey
- N10T143U14.DA 1405mm - 4017lm Black
- N10T163U30.DA 1690mm - 4821lm White
- N10T163U02.DA 1690mm - 4821lm Anodized Grey
- N10T163U14.DA 1690mm - 4821lm Black
- N10T193U30.DA 1970mm - 5624lm White
- N10T193U02.DA 1970mm - 5624lm Anodized Grey
- N10T193U14.DA 1970mm - 5624lm Black
- N10T253U30.DA 2530mm - 7231lm White
- N10T253U02.DA 2530mm - 7231lm Anodized Grey
- N10T253U14.DA 2530mm - 7231lm Black
- N10T303U30.DA 3095mm - 8838lm White
- N10T303U02.DA 3095mm - 8838lm Anodized Grey
- N10T303U14.DA 3095mm - 8838lm Black
- N10TFC3U30.DA Flat Corner - 3214lm White
- N10TFC3U02.DA Flat Corner - 3214lm Anodized Grey
- N10TFC3U14.DA Flat Corner - 3214lm Black
- N10TDC3U30.DA Dihedral Corner - 3214lm White
- N10TDC3U02.DA Dihedral Corner - 3214lm Anodized Grey
- N10TDC3U14.DA Dihedral Corner - 3214lm Black
- N10TEM3U30.DA Emergency - 4017lm White
- N10TEM3U02.DA Emergency - 4017lm Anodized Grey
- N10TEM3U14.DA Emergency - 4017lm Black