


IN-FINITY 100 RECESSED TRIM 4000K GENERAL LIGHTING

Number of heads	1
Mounting	Recessed Trim
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Recessed Trim 4000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Recessed depth (mm)	135
Construction material	Aluminium



- NI0T054G30 565mm - 1555lm White
- NI0T054G02 565mm - 1555lm Anodized Grey
- NI0T054G14 565mm - 1555lm Black
- NI0T084G30 845mm - 2333lm White
- NI0T084G02 845mm - 2333lm Anodized Grey
- NI0T084G14 845mm - 2333lm Black
- NI0T114G30 1125mm - 3111lm White
- NI0T114G02 1125mm - 3111lm Anodized Grey
- NI0T114G14 1125mm - 3111lm Black
- NI0T144G30 1405mm - 3889lm White
- NI0T144G02 1405mm - 3889lm Anodized Grey
- NI0T144G14 1405mm - 3889lm Black
- NI0T164G30 1690mm - 4667lm White
- NI0T164G02 1690mm - 4667lm Anodized Grey
- NI0T164G14 1690mm - 4667lm Black
- NI0T194G30 1970mm - 5445lm White
- NI0T194G02 1970mm - 5445lm Anodized Grey
- NI0T194G14 1970mm - 5445lm Black
- NI0T254G30 2530mm - 7001lm White
- NI0T254G02 2530mm - 7001lm Anodized Grey
- NI0T254G14 2530mm - 7001lm Black
- NI0T304G30 3095mm - 8557lm White
- NI0T304G02 3095mm - 8557lm Anodized Grey
- NI0T304G14 3095mm - 8557lm Black
- NI0TFC4G30 Flat Corner - 3111lm White
- NI0TFC4G02 Flat Corner - 3111lm Anodized Grey
- NI0TFC4G14 Flat Corner - 3111lm Black
- NI0TDC4G30 Dihedral Corner - 3111lm White
- NI0TDC4G02 Dihedral Corner - 3111lm Anodized Grey
- NI0TDC4G14 Dihedral Corner - 3111lm Black
- NI0TEM4G30 Emergency - 3889lm White
- NI0TEM4G02 Emergency - 3889lm Anodized Grey
- NI0TEM4G14 Emergency - 3889lm Black

In-Finity 100 Recessed Trim 4000K General Lighting . Accessories


Structural



- 08.9055.40
- 08.9055.02
- 08.9055.NS

Metal cover. Recessed Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 100 Recessed Trim 4000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

In-Finity 100 Recessed Trim 4000K General Lighting . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- NI0T054G30 565mm - 1555lm White
- NI0T054G02 565mm - 1555lm Anodized Grey
- NI0T054G14 565mm - 1555lm Black
- NI0T084G30 845mm - 2333lm White
- NI0T084G02 845mm - 2333lm Anodized Grey
- NI0T084G14 845mm - 2333lm Black
- NI0T114G30 1125mm - 3111lm White
- NI0T114G02 1125mm - 3111lm Anodized Grey
- NI0T114G14 1125mm - 3111lm Black
- NI0T144G30 1405mm - 3889lm White
- NI0T144G02 1405mm - 3889lm Anodized Grey
- NI0T144G14 1405mm - 3889lm Black
- NI0T164G30 1690mm - 4667lm White
- NI0T164G02 1690mm - 4667lm Anodized Grey
- NI0T164G14 1690mm - 4667lm Black
- NI0T194G30 1970mm - 5445lm White
- NI0T194G02 1970mm - 5445lm Anodized Grey
- NI0T194G14 1970mm - 5445lm Black
- NI0T254G30 2530mm - 7001lm White
- NI0T254G02 2530mm - 7001lm Anodized Grey
- NI0T254G14 2530mm - 7001lm Black
- NI0T304G30 3095mm - 8557lm White
- NI0T304G02 3095mm - 8557lm Anodized Grey
- NI0T304G14 3095mm - 8557lm Black
- NI0TFC4G30 Flat Corner - 3111lm White
- NI0TFC4G02 Flat Corner - 3111lm Anodized Grey
- NI0TFC4G14 Flat Corner - 3111lm Black
- NI0TDC4G30 Dihedral Corner - 3111lm White
- NI0TDC4G02 Dihedral Corner - 3111lm Anodized Grey
- NI0TDC4G14 Dihedral Corner - 3111lm Black
- NI0TEM4G30 Emergency - 3889lm White
- NI0TEM4G02 Emergency - 3889lm Anodized Grey
- NI0TEM4G14 Emergency - 3889lm Black