

IN-FINITY 100 RECESSED TRIM 4000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Recessed Trim
Lamps description	Top LED 34,1W/m 4228 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Recessed Trim 4000K General Lighting Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	109°

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N10T054G30.DA 565mm - 1555lm White
- N10T054G02.DA 565mm - 1555lm Anodized Grey
- N10T054G14.DA 565mm - 1555lm Black
- N10T084G30.DA 845mm - 2333lm White
- N10T084G02.DA 845mm - 2333lm Anodized Grey
- N10T084G14.DA 845mm - 2333lm Black
- N10T114G30.DA 1125mm - 3111lm White
- N10T114G02.DA 1125mm - 3111lm Anodized Grey
- N10T114G14.DA 1125mm - 3111lm Black
- N10T144G30.DA 1405mm - 3889lm White
- N10T144G02.DA 1405mm - 3889lm Anodized Grey
- N10T144G14.DA 1405mm - 3889lm Black
- N10T164G30.DA 1690mm - 4667lm White
- N10T164G02.DA 1690mm - 4667lm Anodized Grey
- N10T164G14.DA 1690mm - 4667lm Black
- N10T194G30.DA 1970mm - 5445lm White
- N10T194G02.DA 1970mm - 5445lm Anodized Grey
- N10T194G14.DA 1970mm - 5445lm Black
- N10T254G30.DA 2530mm - 7001lm White
- N10T254G02.DA 2530mm - 7001lm Anodized Grey
- N10T254G14.DA 2530mm - 7001lm Black
- N10T304G30.DA 3095mm - 8557lm White
- N10T304G02.DA 3095mm - 8557lm Anodized Grey
- N10T304G14.DA 3095mm - 8557lm Black
- N10TFC4G30.DA Flat Corner - 3111lm White
- N10TFC4G02.DA Flat Corner - 3111lm Anodized Grey
- N10TFC4G14.DA Flat Corner - 3111lm Black
- N10TDC4G30.DA Dihedral Corner - 3111lm White
- N10TDC4G02.DA Dihedral Corner - 3111lm Anodized Grey
- N10TDC4G14.DA Dihedral Corner - 3111lm Black
- N10TEM4G30.DA Emergency - 3889lm White
- N10TEM4G02.DA Emergency - 3889lm Anodized Grey
- N10TEM4G14.DA Emergency - 3889lm Black

PHYSICAL

Recessed depth (mm)	135
Construction material	Aluminium



In-Finity 100 Recessed Trim 4000K General Lighting Dali . Accessories

Structural



- 08.9055.40
- 08.9055.02
- 08.9055.NS

Metal cover. Recessed Trim. 100 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 100 Recessed Trim 4000K General Lighting Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 100 Recessed Trim 4000K General Lighting Dali designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N10T054G30.DA 565mm - 1555lm White
- N10T054G02.DA 565mm - 1555lm Anodized Grey
- N10T054G14.DA 565mm - 1555lm Black
- N10T084G30.DA 845mm - 2333lm White
- N10T084G02.DA 845mm - 2333lm Anodized Grey
- N10T084G14.DA 845mm - 2333lm Black
- N10T114G30.DA 1125mm - 3111lm White
- N10T114G02.DA 1125mm - 3111lm Anodized Grey
- N10T114G14.DA 1125mm - 3111lm Black
- N10T144G30.DA 1405mm - 3889lm White
- N10T144G02.DA 1405mm - 3889lm Anodized Grey
- N10T144G14.DA 1405mm - 3889lm Black
- N10T164G30.DA 1690mm - 4667lm White
- N10T164G02.DA 1690mm - 4667lm Anodized Grey
- N10T164G14.DA 1690mm - 4667lm Black
- N10T194G30.DA 1970mm - 5445lm White
- N10T194G02.DA 1970mm - 5445lm Anodized Grey
- N10T194G14.DA 1970mm - 5445lm Black
- N10T254G30.DA 2530mm - 7001lm White
- N10T254G02.DA 2530mm - 7001lm Anodized Grey
- N10T254G14.DA 2530mm - 7001lm Black
- N10T304G30.DA 3095mm - 8557lm White
- N10T304G02.DA 3095mm - 8557lm Anodized Grey
- N10T304G14.DA 3095mm - 8557lm Black
- N10TFC4G30.DA Flat Corner - 3111lm White
- N10TFC4G02.DA Flat Corner - 3111lm Anodized Grey
- N10TFC4G14.DA Flat Corner - 3111lm Black
- N10TDC4G30.DA Dihedral Corner - 3111lm White
- N10TDC4G02.DA Dihedral Corner - 3111lm Anodized Grey
- N10TDC4G14.DA Dihedral Corner - 3111lm Black
- N10TEM4G30.DA Emergency - 3889lm White
- N10TEM4G02.DA Emergency - 3889lm Anodized Grey
- N10TEM4G14.DA Emergency - 3889lm Black