


IN-FINITY 100 SUSPENSION UP & DOWN 3000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 46,9W/m 3000K CRI 80 1536 lm/m UP - 3915 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 100 Suspension Up & Down 3000K General Lighting Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	109°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N10U113G30.DA 1125mm - 4220lm **White**
- N10U113G02.DA 1125mm - 4220lm **Anodized Grey**
- N10U113G14.DA 1125mm - 4220lm **Black**
- N10U143G30.DA 1405mm - 5275lm **White**
- N10U143G02.DA 1405mm - 5275lm **Anodized Grey**
- N10U143G14.DA 1405mm - 5275lm **Black**
- N10U193G30.DA 1970mm - 7386lm **White**
- N10U193G02.DA 1970mm - 7386lm **Anodized Grey**
- N10U193G14.DA 1970mm - 7386lm **Black**
- N10U303G30.DA 3095mm - 11606lm **White**
- N10U303G02.DA 3095mm - 11606lm **Anodized Grey**
- N10U303G14.DA 3095mm - 11606lm **Black**
- N10UFC3G30.DA Flat Corner - 4220lm **White**
- N10UFC3G02.DA Flat Corner - 4220lm **Anodized Grey**
- N10UFC3G14.DA Flat Corner - 4220lm **Black**
- N10UEM3G30.DA Emergency - 5275lm **White**
- N10UEM3G02.DA Emergency - 5275lm **Anodized Grey**
- N10UEM3G14.DA Emergency - 5275lm **Black**
- N10U083G30.DA 845mm - 3165lm **White**
- N10U083G02.DA 845mm - 3165lm **Anodized Grey**
- N10U083G14.DA 845mm - 3165lm **Black**
- N10U163G30.DA 1690mm - 6330lm **White**
- N10U163G02.DA 1690mm - 6330lm **Anodized Grey**
- N10U163G14.DA 1690mm - 6330lm **Black**
- N10U253G30.DA 2530mm - 9496lm **White**
- N10U253G02.DA 2530mm - 9496lm **Anodized Grey**
- N10U253G14.DA 2530mm - 9496lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 100 Suspension Up & Down 3000K General Lighting Dali . Accessories

Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.




In-Finity 100 Suspension Up & Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U113G30.DA | 1125mm - 4220lm **White**
- N10U113G02.DA | 1125mm - 4220lm **Anodized Grey**
- N10U113G14.DA | 1125mm - 4220lm **Black**
- N10U143G30.DA | 1405mm - 5275lm **White**
- N10U143G02.DA | 1405mm - 5275lm **Anodized Grey**
- N10U143G14.DA | 1405mm - 5275lm **Black**
- N10U193G30.DA | 1970mm - 7386lm **White**
- N10U193G02.DA | 1970mm - 7386lm **Anodized Grey**
- N10U193G14.DA | 1970mm - 7386lm **Black**
- N10U303G30.DA | 3095mm - 11606lm **White**
- N10U303G02.DA | 3095mm - 11606lm **Anodized Grey**
- N10U303G14.DA | 3095mm - 11606lm **Black**
- N10UFC3G30.DA Flat Corner - 4220lm **White**
- N10UFC3G02.DA Flat Corner - 4220lm **Anodized Grey**
- N10UFC3G14.DA Flat Corner - 4220lm **Black**
- N10UEM3G30.DA Emergency - 5275lm **White**
- N10UEM3G02.DA Emergency - 5275lm **Anodized Grey**
- N10UEM3G14.DA Emergency - 5275lm **Black**
- N10U083G30.DA 845mm - 3165lm **White**
- N10U083G02.DA 845mm - 3165lm **Anodized Grey**
- N10U083G14.DA 845mm - 3165lm **Black**
- N10U163G30.DA 1690mm - 6330lm **White**
- N10U163G02.DA 1690mm - 6330lm **Anodized Grey**
- N10U163G14.DA 1690mm - 6330lm **Black**
- N10U253G30.DA 2530mm - 9496lm **White**
- N10U253G02.DA 2530mm - 9496lm **Anodized Grey**
- N10U253G14.DA 2530mm - 9496lm **Black**



In-Finity 100 Suspension Up & Down 3000K General Lighting Dali . Accessories


Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 100 Suspension Up & Down 3000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

In-Finity 100 Suspension Up & Down 3000K General Lighting Dali . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N10U113G30.DA | 125mm - 4220lm White
- N10U113G02.DA | 125mm - 4220lm Anodized Grey
- N10U113G14.DA | 125mm - 4220lm Black
- N10U143G30.DA | 1405mm - 5275lm White
- N10U143G02.DA | 1405mm - 5275lm Anodized Grey
- N10U143G14.DA | 1405mm - 5275lm Black
- N10U193G30.DA | 1970mm - 7386lm White
- N10U193G02.DA | 1970mm - 7386lm Anodized Grey
- N10U193G14.DA | 1970mm - 7386lm Black
- N10U303G30.DA | 3095mm - 11606lm White
- N10U303G02.DA | 3095mm - 11606lm Anodized Grey
- N10U303G14.DA | 3095mm - 11606lm Black
- N10UFC3G30.DA Flat Corner - 4220lm White
- N10UFC3G02.DA Flat Corner - 4220lm Anodized Grey
- N10UFC3G14.DA Flat Corner - 4220lm Black
- N10UEM3G30.DA Emergency - 5275lm White
- N10UEM3G02.DA Emergency - 5275lm Anodized Grey
- N10UEM3G14.DA Emergency - 5275lm Black
- N10U083G30.DA | 845mm - 3165lm White
- N10U083G02.DA | 845mm - 3165lm Anodized Grey
- N10U083G14.DA | 845mm - 3165lm Black
- N10U163G30.DA | 1690mm - 6330lm White
- N10U163G02.DA | 1690mm - 6330lm Anodized Grey
- N10U163G14.DA | 1690mm - 6330lm Black
- N10U253G30.DA | 2530mm - 9496lm White
- N10U253G02.DA | 2530mm - 9496lm Anodized Grey
- N10U253G14.DA | 2530mm - 9496lm Black

