


## IN-FINITY 100 SUSPENSION UP & DOWN 4000K GENERAL LIGHTING DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant up & down
<b>Lamps description</b>	Top LED 46,9W/m 4000K CRI 80 1680 lm/m UP - 4228 lm/m DOWN
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1125 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 100 Suspension Up & Down 4000K General Lighting Dali**  
designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Direct - Indirect
<b>Beam angle</b>	109°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N10U114G30.DA 1125mm - 4282lm **White**
- N10U114G02.DA 1125mm - 4282lm **Anodized Grey**
- N10U114G14.DA 1125mm - 4282lm **Black**
- N10U144G30.DA 1405mm - 5353lm **White**
- N10U144G02.DA 1405mm - 5353lm **Anodized Grey**
- N10U144G14.DA 1405mm - 5353lm **Black**
- N10U194G30.DA 1970mm - 7494lm **White**
- N10U194G02.DA 1970mm - 7494lm **Anodized Grey**
- N10U194G14.DA 1970mm - 7494lm **Black**
- N10U304G30.DA 3095mm - 11777lm **White**
- N10U304G02.DA 3095mm - 11777lm **Anodized Grey**
- N10U304G14.DA 3095mm - 11777lm **Black**
- N10UFC4G30.DA Flat Corner - 4282lm **White**
- N10UFC4G02.DA Flat Corner - 4282lm **Anodized Grey**
- N10UFC4G14.DA Flat Corner - 4282lm **Black**
- N10UEM4G30.DA Emergency - 5353lm **White**
- N10UEM4G02.DA Emergency - 5353lm **Anodized Grey**
- N10UEM4G14.DA Emergency - 5353lm **Black**
- N10U084G30.DA 845mm - 3212lm **White**
- N10U084G02.DA 845mm - 3212lm **Anodized Grey**
- N10U084G14.DA 845mm - 3212lm **Black**
- N10U164G30.DA 1690mm - 6424lm **White**
- N10U164G02.DA 1690mm - 6424lm **Anodized Grey**
- N10U164G14.DA 1690mm - 6424lm **Black**
- N10U254G30.DA 2530mm - 9636lm **White**
- N10U254G02.DA 2530mm - 9636lm **Anodized Grey**
- N10U254G14.DA 2530mm - 9636lm **Black**

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 100 Suspension Up & Down 4000K General Lighting Dali . Accessories

### Structural



- 08.9058.40
- 08.9058.02
- 08.9058.NS
- 08.9058.06

#### Metal cover. Suspension Up & Down. 100 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.




### In-Finity 100 Suspension Up & Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N10U114G30.DA | 125mm - 4282lm **White**
- N10U114G02.DA | 125mm - 4282lm **Anodized Grey**
- N10U114G14.DA | 125mm - 4282lm **Black**
- N10U144G30.DA | 1405mm - 5353lm **White**
- N10U144G02.DA | 1405mm - 5353lm **Anodized Grey**
- N10U144G14.DA | 1405mm - 5353lm **Black**
- N10U194G30.DA | 1970mm - 7494lm **White**
- N10U194G02.DA | 1970mm - 7494lm **Anodized Grey**
- N10U194G14.DA | 1970mm - 7494lm **Black**
- N10U304G30.DA | 3095mm - 11777lm **White**
- N10U304G02.DA | 3095mm - 11777lm **Anodized Grey**
- N10U304G14.DA | 3095mm - 11777lm **Black**
- N10UFC4G30.DA Flat Corner - 4282lm **White**
- N10UFC4G02.DA Flat Corner - 4282lm **Anodized Grey**
- N10UFC4G14.DA Flat Corner - 4282lm **Black**
- N10UEM4G30.DA Emergency - 5353lm **White**
- N10UEM4G02.DA Emergency - 5353lm **Anodized Grey**
- N10UEM4G14.DA Emergency - 5353lm **Black**
- N10U084G30.DA 845mm - 3212lm **White**
- N10U084G02.DA 845mm - 3212lm **Anodized Grey**
- N10U084G14.DA 845mm - 3212lm **Black**
- N10U164G30.DA 1690mm - 6424lm **White**
- N10U164G02.DA 1690mm - 6424lm **Anodized Grey**
- N10U164G14.DA 1690mm - 6424lm **Black**
- N10U254G30.DA 2530mm - 9636lm **White**
- N10U254G02.DA 2530mm - 9636lm **Anodized Grey**
- N10U254G14.DA 2530mm - 9636lm **Black**



## In-Finity 100 Suspension Up & Down 4000K General Lighting Dali . Accessories


### Electrical



08.0031.00.DA

#### Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



### In-Finity 100 Suspension Up & Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

## In-Finity 100 Suspension Up & Down 4000K General Lighting Dali . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED

- N10U114G30.DA | 125mm - 4282lm **White**
- N10U114G02.DA | 125mm - 4282lm **Anodized Grey**
- N10U114G14.DA | 125mm - 4282lm **Black**
- N10U144G30.DA | 1405mm - 5353lm **White**
- N10U144G02.DA | 1405mm - 5353lm **Anodized Grey**
- N10U144G14.DA | 1405mm - 5353lm **Black**
- N10U194G30.DA | 1970mm - 7494lm **White**
- N10U194G02.DA | 1970mm - 7494lm **Anodized Grey**
- N10U194G14.DA | 1970mm - 7494lm **Black**
- N10U304G30.DA | 3095mm - 11777lm **White**
- N10U304G02.DA | 3095mm - 11777lm **Anodized Grey**
- N10U304G14.DA | 3095mm - 11777lm **Black**
- N10UFC4G30.DA Flat Corner - 4282lm **White**
- N10UFC4G02.DA Flat Corner - 4282lm **Anodized Grey**
- N10UFC4G14.DA Flat Corner - 4282lm **Black**
- N10UEM4G30.DA Emergency - 5353lm **White**
- N10UEM4G02.DA Emergency - 5353lm **Anodized Grey**
- N10UEM4G14.DA Emergency - 5353lm **Black**
- N10U084G30.DA | 845mm - 3212lm **White**
- N10U084G02.DA | 845mm - 3212lm **Anodized Grey**
- N10U084G14.DA | 845mm - 3212lm **Black**
- N10U164G30.DA | 1690mm - 6424lm **White**
- N10U164G02.DA | 1690mm - 6424lm **Anodized Grey**
- N10U164G14.DA | 1690mm - 6424lm **Black**
- N10U254G30.DA | 2530mm - 9636lm **White**
- N10U254G02.DA | 2530mm - 9636lm **Anodized Grey**
- N10U254G14.DA | 2530mm - 9636lm **Black**

