


IN-FINITY 35 SUSPENSION DOWN 3000K GENERAL LIGHTING

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 19,8W/m 2558 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	110°

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



- N35D053G30B 565mm - 657lm White
- N35D053G02B 565mm - 657lm Anodized Grey
- N35D053G14B 565mm - 657lm Black
- N35D083G30B 845mm - 986lm White
- N35D083G02B 845mm - 986lm Anodized Grey
- N35D083G14B 845mm - 986lm Black
- N35D113G30B 1125mm - 1315lm White
- N35D113G02B 1125mm - 1315lm Anodized Grey
- N35D113G14B 1125mm - 1315lm Black
- N35D143G30B 1405mm - 1643lm White
- N35D143G02B 1405mm - 1643lm Anodized Grey
- N35D143G14B 1405mm - 1643lm Black
- N35D163G30B 1690mm - 1972lm White
- N35D163G02B 1690mm - 1972lm Anodized Grey
- N35D163G14B 1690mm - 1972lm Black
- N35D193G30B 1970mm - 2301lm White
- N35D193G02B 1970mm - 2301lm Anodized Grey
- N35D193G14B 1970mm - 2301lm Black
- N35D253G30B 2530mm - 2958lm White
- N35D253G02B 2530mm - 2958lm Anodized Grey
- N35D253G14B 2530mm - 2958lm Black
- N35D303G30B 3095mm - 3616lm White
- N35D303G02B 3095mm - 3616lm Anodized Grey
- N35D303G14B 3095mm - 3616lm Black
- N35DFC3G30B Flat Corner - 1315lm White
- N35DFC3G02B Flat Corner - 1315lm Anodized Grey
- N35DFC3G14B Flat Corner - 1315lm Black
- N35DEM3G30B Emergency - 1643lm White
- N35DEM3G02B Emergency - 1643lm Anodized Grey
- N35DEM3G14B Emergency - 1643lm Black

In-Finity 35 Suspension Down 3000K General Lighting . Accessories

Structural



- 08.9050.40
- 08.9050.02
- 08.9050.NS
- 08.9050.06

Metal cover. Surface / Suspension Down. 35 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 35 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N35D053G30B 565mm - 657lm White
- N35D053G02B 565mm - 657lm Anodized Grey
- N35D053G14B 565mm - 657lm Black
- N35D083G30B 845mm - 986lm White
- N35D083G02B 845mm - 986lm Anodized Grey
- N35D083G14B 845mm - 986lm Black
- N35D113G30B 1125mm - 1315lm White
- N35D113G02B 1125mm - 1315lm Anodized Grey
- N35D113G14B 1125mm - 1315lm Black
- N35D143G30B 1405mm - 1643lm White
- N35D143G02B 1405mm - 1643lm Anodized Grey
- N35D143G14B 1405mm - 1643lm Black
- N35D163G30B 1690mm - 1972lm White
- N35D163G02B 1690mm - 1972lm Anodized Grey
- N35D163G14B 1690mm - 1972lm Black
- N35D193G30B 1970mm - 2301lm White
- N35D193G02B 1970mm - 2301lm Anodized Grey
- N35D193G14B 1970mm - 2301lm Black
- N35D253G30B 2530mm - 2958lm White
- N35D253G02B 2530mm - 2958lm Anodized Grey
- N35D253G14B 2530mm - 2958lm Black
- N35D303G30B 3095mm - 3616lm White
- N35D303G02B 3095mm - 3616lm Anodized Grey
- N35D303G14B 3095mm - 3616lm Black
- N35DFC3G30B Flat Corner - 1315lm White
- N35DFC3G02B Flat Corner - 1315lm Anodized Grey
- N35DFC3G14B Flat Corner - 1315lm Black
- N35DEM3G30B Emergency - 1643lm White
- N35DEM3G02B Emergency - 1643lm Anodized Grey
- N35DEM3G14B Emergency - 1643lm Black

In-Finity 35 Suspension Down 3000K General Lighting . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



In-Finity 35 Suspension Down 3000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

In-Finity 35 Suspension Down 3000K General Lighting . Lamps



Top LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED

- N35D053G30B 565mm - 657lm White
- N35D053G02B 565mm - 657lm Anodized Grey
- N35D053G14B 565mm - 657lm Black
- N35D083G30B 845mm - 986lm White
- N35D083G02B 845mm - 986lm Anodized Grey
- N35D083G14B 845mm - 986lm Black
- N35D113G30B 1125mm - 1315lm White
- N35D113G02B 1125mm - 1315lm Anodized Grey
- N35D113G14B 1125mm - 1315lm Black
- N35D143G30B 1405mm - 1643lm White
- N35D143G02B 1405mm - 1643lm Anodized Grey
- N35D143G14B 1405mm - 1643lm Black
- N35D163G30B 1690mm - 1972lm White
- N35D163G02B 1690mm - 1972lm Anodized Grey
- N35D163G14B 1690mm - 1972lm Black
- N35D193G30B 1970mm - 2301lm White
- N35D193G02B 1970mm - 2301lm Anodized Grey
- N35D193G14B 1970mm - 2301lm Black
- N35D253G30B 2530mm - 2958lm White
- N35D253G02B 2530mm - 2958lm Anodized Grey
- N35D253G14B 2530mm - 2958lm Black
- N35D303G30B 3095mm - 3616lm White
- N35D303G02B 3095mm - 3616lm Anodized Grey
- N35D303G14B 3095mm - 3616lm Black
- N35DFC3G30B Flat Corner - 1315lm White
- N35DFC3G02B Flat Corner - 1315lm Anodized Grey
- N35DFC3G14B Flat Corner - 1315lm Black
- N35DEM3G30B Emergency - 1643lm White
- N35DEM3G02B Emergency - 1643lm Anodized Grey
- N35DEM3G14B Emergency - 1643lm Black