


## IN-FINITY 35 SUSPENSION DOWN 4000K GENERAL LIGHTING

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant
<b>Lamps description</b>	Top LED 19,8W/m 2761 lm/m 4000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



### In-Finity 35 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	110°

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



- N35D054G30B 565mm - 712lm White
- N35D054G02B 565mm - 712lm Anodized Grey
- N35D054G14B 565mm - 712lm Black
- N35D084G30B 845mm - 1068lm White
- N35D084G02B 845mm - 1068lm Anodized Grey
- N35D084G14B 845mm - 1068lm Black
- N35D114G30B 1125mm - 1424lm White
- N35D114G02B 1125mm - 1424lm Anodized Grey
- N35D114G14B 1125mm - 1424lm Black
- N35D144G30B 1405mm - 1779lm White
- N35D144G02B 1405mm - 1779lm Anodized Grey
- N35D144G14B 1405mm - 1779lm Black
- N35D164G30B 1690mm - 2135lm White
- N35D164G14B 1690mm - 2135lm Black
- N35D164G02B 1690mm - 2135lm Anodized Grey
- N35D194G30B 1970mm - 2491lm White
- N35D194G02B 1970mm - 2491lm Anodized Grey
- N35D194G14B 1970mm - 2491lm Black
- N35D254G30B 2530mm - 3203lm White
- N35D254G02B 2530mm - 3203lm Anodized Grey
- N35D254G14B 2530mm - 3203lm Black
- N35D304G30B 3095mm - 3915lm White
- N35D304G02B 3095mm - 3915lm Anodized Grey
- N35D304G14B 3095mm - 3915lm Black
- N35DFC4G30B Flat Corner - 1424lm White
- N35DFC4G02B Flat Corner - 1424lm Anodized Grey
- N35DFC4G14B Flat Corner - 1424lm Black
- N35DEM4G30B Emergency - 1779lm White
- N35DEM4G02B Emergency - 1779lm Anodized Grey
- N35DEM4G14B Emergency - 1779lm Black

## In-Finity 35 Suspension Down 4000K General Lighting . Accessories

### Structural



- 08.9050.40
- 08.9050.02
- 08.9050.NS
- 08.9050.06

#### Metal cover. Surface / Suspension Down. 35 mm

Metal cover for the different profiles. 2 unit kit.

### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 35 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N35D054G30B 565mm - 712lm White
- N35D054G02B 565mm - 712lm Anodized Grey
- N35D054G14B 565mm - 712lm Black
- N35D084G30B 845mm - 1068lm White
- N35D084G02B 845mm - 1068lm Anodized Grey
- N35D084G14B 845mm - 1068lm Black
- N35D114G30B 1125mm - 1424lm White
- N35D114G02B 1125mm - 1424lm Anodized Grey
- N35D114G14B 1125mm - 1424lm Black
- N35D144G30B 1405mm - 1779lm White
- N35D144G02B 1405mm - 1779lm Anodized Grey
- N35D144G14B 1405mm - 1779lm Black
- N35D164G30B 1690mm - 2135lm White
- N35D164G14B 1690mm - 2135lm Black
- N35D164G02B 1690mm - 2135lm Anodized Grey
- N35D194G30B 1970mm - 2491lm White
- N35D194G02B 1970mm - 2491lm Anodized Grey
- N35D194G14B 1970mm - 2491lm Black
- N35D254G30B 2530mm - 3203lm White
- N35D254G02B 2530mm - 3203lm Anodized Grey
- N35D254G14B 2530mm - 3203lm Black
- N35D304G30B 3095mm - 3915lm White
- N35D304G02B 3095mm - 3915lm Anodized Grey
- N35D304G14B 3095mm - 3915lm Black
- N35DFC4G30B Flat Corner - 1424lm White
- N35DFC4G02B Flat Corner - 1424lm Anodized Grey
- N35DFC4G14B Flat Corner - 1424lm Black
- N35DEM4G30B Emergency - 1779lm White
- N35DEM4G02B Emergency - 1779lm Anodized Grey
- N35DEM4G14B Emergency - 1779lm Black

## In-Finity 35 Suspension Down 4000K General Lighting . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



### In-Finity 35 Suspension Down 4000K General Lighting

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

## In-Finity 35 Suspension Down 4000K General Lighting . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED

- N35D054G30B 565mm - 712lm White
- N35D054G02B 565mm - 712lm Anodized Grey
- N35D054G14B 565mm - 712lm Black
- N35D084G30B 845mm - 1068lm White
- N35D084G02B 845mm - 1068lm Anodized Grey
- N35D084G14B 845mm - 1068lm Black
- N35D114G30B 1125mm - 1424lm White
- N35D114G02B 1125mm - 1424lm Anodized Grey
- N35D114G14B 1125mm - 1424lm Black
- N35D144G30B 1405mm - 1779lm White
- N35D144G02B 1405mm - 1779lm Anodized Grey
- N35D144G14B 1405mm - 1779lm Black
- N35D164G30B 1690mm - 2135lm White
- N35D164G14B 1690mm - 2135lm Black
- N35D164G02B 1690mm - 2135lm Anodized Grey
- N35D194G30B 1970mm - 2491lm White
- N35D194G02B 1970mm - 2491lm Anodized Grey
- N35D194G14B 1970mm - 2491lm Black
- N35D254G30B 2530mm - 3203lm White
- N35D254G02B 2530mm - 3203lm Anodized Grey
- N35D254G14B 2530mm - 3203lm Black
- N35D304G30B 3095mm - 3915lm White
- N35D304G02B 3095mm - 3915lm Anodized Grey
- N35D304G14B 3095mm - 3915lm Black
- N35DFC4G30B Flat Corner - 1424lm White
- N35DFC4G02B Flat Corner - 1424lm Anodized Grey
- N35DFC4G14B Flat Corner - 1424lm Black
- N35DEM4G30B Emergency - 1779lm White
- N35DEM4G02B Emergency - 1779lm Anodized Grey
- N35DEM4G14B Emergency - 1779lm Black