


## IN-FINITY 35 SUSPENSION DOWN 4000K MICRO-PRISMATIC DIFFUSER DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant
<b>Lamps description</b>	Top LED 19,8W/m 2761 lm/m 4000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali**

designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	76°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N35D054U30BDA 565mm - 553lm White
- N35D054U02BDA 565mm - 553lm Anodized Grey
- N35D054U14BDA 565mm - 553lm Black
- N35D084U30BDA 845mm - 830lm White
- N35D084U02BDA 845mm - 830lm Anodized Grey
- N35D084U14BDA 845mm - 830lm Black
- N35D114U30BDA 1125mm - 1107lm White
- N35D114U02BDA 1125mm - 1107lm Anodized Grey
- N35D114U14BDA 1125mm - 1107lm Black
- N35D144U30BDA 1405mm - 1384lm White
- N35D144U02BDA 1405mm - 1384lm Anodized Grey
- N35D144U14BDA 1405mm - 1384lm Black
- N35D164U30BDA 1690mm - 1660lm White
- N35D164U02BDA 1690mm - 1660lm Anodized Grey
- N35D164U14BDA 1690mm - 1660lm Black
- N35D194U30BDA 1970mm - 1937lm White
- N35D194U02BDA 1970mm - 1937lm Anodized Grey
- N35D194U14BDA 1970mm - 1937lm Black
- N35D254U30BDA 2530mm - 2491lm White
- N35D254U02BDA 2530mm - 2491lm Anodized Grey
- N35D254U14BDA 2530mm - 2491lm Black
- N35D304U30BDA 3095mm - 3044lm White
- N35D304U02BDA 3095mm - 3044lm Anodized Grey
- N35D304U14BDA 3095mm - 3044lm Black
- N35DFC4U30BDA Flat Corner - 1107lm White
- N35DFC4U02BDA Flat Corner - 1107lm Anodized Grey
- N35DFC4U14BDA Flat Corner - 1107lm Black
- N35DEM4U30BDA Emergency - 1384lm White
- N35DEM4U02BDA Emergency - 1384lm Anodized Grey
- N35DEM4U14BDA Emergency - 1384lm Black

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Accessories


### Structural



- 08.9050.40
- 08.9050.02
- 08.9050.NS
- 08.9050.06

#### Metal cover. Surface / Suspension Down. 35 mm

Metal cover for the different profiles. 2 unit kit.



### In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N35D054U30BDA 565mm - 553lm White
- N35D054U02BDA 565mm - 553lm Anodized Grey
- N35D054U14BDA 565mm - 553lm Black
- N35D084U30BDA 845mm - 830lm White
- N35D084U02BDA 845mm - 830lm Anodized Grey
- N35D084U14BDA 845mm - 830lm Black
- N35D114U30BDA 1125mm - 1107lm White
- N35D114U02BDA 1125mm - 1107lm Anodized Grey
- N35D114U14BDA 1125mm - 1107lm Black
- N35D144U30BDA 1405mm - 1384lm White
- N35D144U02BDA 1405mm - 1384lm Anodized Grey
- N35D144U14BDA 1405mm - 1384lm Black
- N35D164U30BDA 1690mm - 1660lm White
- N35D164U02BDA 1690mm - 1660lm Anodized Grey
- N35D164U14BDA 1690mm - 1660lm Black
- N35D194U30BDA 1970mm - 1937lm White
- N35D194U02BDA 1970mm - 1937lm Anodized Grey
- N35D194U14BDA 1970mm - 1937lm Black
- N35D254U30BDA 2530mm - 2491lm White
- N35D254U02BDA 2530mm - 2491lm Anodized Grey
- N35D254U14BDA 2530mm - 2491lm Black
- N35D304U30BDA 3095mm - 3044lm White
- N35D304U02BDA 3095mm - 3044lm Anodized Grey
- N35D304U14BDA 3095mm - 3044lm Black
- N35DFC4U30BDA Flat Corner - 1107lm White
- N35DFC4U02BDA Flat Corner - 1107lm Anodized Grey
- N35DFC4U14BDA Flat Corner - 1107lm Black
- N35DEM4U30BDA Emergency - 1384lm White
- N35DEM4U02BDA Emergency - 1384lm Anodized Grey
- N35DEM4U14BDA Emergency - 1384lm Black

### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m). Maximum distance between the suspension cables: 2 m.

## In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Accessories


### Electrical



08.0031.00.DA

#### Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable



### In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

## In-Finity 35 Suspension Down 4000K Micro-Prismatic Diffuser Dali . Lamps



#### Top LED

#### Lamp category:

LED

#### Socket:

Special base

#### Lamp type:

Top LED

- N35D054U30BDA 565mm - 553lm White
- N35D054U02BDA 565mm - 553lm Anodized Grey
- N35D054U14BDA 565mm - 553lm Black
- N35D084U30BDA 845mm - 830lm White
- N35D084U02BDA 845mm - 830lm Anodized Grey
- N35D084U14BDA 845mm - 830lm Black
- N35D114U30BDA 1125mm - 1107lm White
- N35D114U02BDA 1125mm - 1107lm Anodized Grey
- N35D114U14BDA 1125mm - 1107lm Black
- N35D144U30BDA 1405mm - 1384lm White
- N35D144U02BDA 1405mm - 1384lm Anodized Grey
- N35D144U14BDA 1405mm - 1384lm Black
- N35D164U30BDA 1690mm - 1660lm White
- N35D164U02BDA 1690mm - 1660lm Anodized Grey
- N35D164U14BDA 1690mm - 1660lm Black
- N35D194U30BDA 1970mm - 1937lm White
- N35D194U02BDA 1970mm - 1937lm Anodized Grey
- N35D194U14BDA 1970mm - 1937lm Black
- N35D254U30BDA 2530mm - 2491lm White
- N35D254U02BDA 2530mm - 2491lm Anodized Grey
- N35D254U14BDA 2530mm - 2491lm Black
- N35D304U30BDA 3095mm - 3044lm White
- N35D304U02BDA 3095mm - 3044lm Anodized Grey
- N35D304U14BDA 3095mm - 3044lm Black
- N35DFC4U30BDA Flat Corner - 1107lm White
- N35DFC4U02BDA Flat Corner - 1107lm Anodized Grey
- N35DFC4U14BDA Flat Corner - 1107lm Black
- N35DEM4U30BDA Emergency - 1384lm White
- N35DEM4U02BDA Emergency - 1384lm Anodized Grey
- N35DEM4U14BDA Emergency - 1384lm Black