

## IN-FINITY 35 RECESSED NO TRIM 3000K MICRO-PRISMATIC DIFFUSER DALI

<b>Number of heads</b>	1
<b>Mounting</b>	Recessed No Trim
<b>Lamps description</b>	Top LED 19,8W/m 2558 lm/m 3000K CRI 80
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Symmetric
<b>Beam angle</b>	76°

### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic dimmable dali
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

### PHYSICAL

<b>Recessed depth (mm)</b>	120
<b>Construction material</b>	Aluminium





### In-Finity 35 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali



designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N35N053U30BDA 565mm - 511lm White
- N35N083U30BDA 845mm - 767lm White
- N35N113U30BDA 1125mm - 1022lm White
- N35N143U30BDA 1405mm - 1278lm White
- N35N163U30BDA 1690mm - 1534lm White
- N35N193U30BDA 1970mm - 1789lm White
- N35N253U30BDA 2530mm - 2300lm White
- N35N303U30BDA 3095mm - 2811lm White
- N35NFC3U30BDA Flat Corner - 1022lm White
- N35NDC3U30BDA Dihedral Corner - 1022lm White
- N35NEM3U30BDA Emergency - 1278lm White



### CERTIFICATIONS



## In-Finity 35 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali . Accessories

### Structural



08.9050.40

#### Metal cover. Recessed No Trim. 35 mm

Metal cover for the different profiles. 2 unit kit.



### In-Finity 35 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali

designed by FLOS Architectural

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

## In-Finity 35 Recessed No Trim 3000K Micro-Prismatic Diffuser Dali . Lamps



#### Top LED

#### Lamp category:

LED


#### Socket:

Special base

#### Lamp type:

Top LED

- N35N053U30BDA 565mm - 511lm White
- N35N083U30BDA 845mm - 767lm White
- N35N113U30BDA 1125mm - 1022lm White
- N35N143U30BDA 1405mm - 1278lm White
- N35N163U30BDA 1690mm - 1534lm White
- N35N193U30BDA 1970mm - 1789lm White
- N35N253U30BDA 2530mm - 2300lm White
- N35N303U30BDA 3095mm - 2811lm White
- N35NFC3U30BDA Flat Corner - 1022lm White
- N35NDC3U30BDA Dihedral Corner - 1022lm White
- N35NEM3U30BDA Emergency - 1278lm White



### CERTIFICATIONS

