


IN-FINITY 35 SURFACE 3000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Surface
Lamps description	Top LED 19,8W/m 2558 lm/m 3000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 35 Surface 3000K Micro-Prismatic Diffuser Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	76°

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N35S053U30BDA 565mm - 511lm White
- N35S053U02BDA 565mm - 511lm Anodized Grey
- N35S053U14BDA 565mm - 511lm Black
- N35S083U30BDA 845mm - 767lm White
- N35S083U02BDA 845mm - 767lm Anodized Grey
- N35S083U14BDA 845mm - 767lm Black
- N35S113U30BDA 1125mm - 1022lm White
- N35S113U02BDA 1125mm - 1022lm Anodized Grey
- N35S113U14BDA 1125mm - 1022lm Black
- N35S143U30BDA 1405mm - 1278lm White
- N35S143U02BDA 1405mm - 1278lm Anodized Grey
- N35S143U14BDA 1405mm - 1278lm Black
- N35S163U30BDA 1690mm - 1534lm White
- N35S163U02BDA 1690mm - 1534lm Anodized Grey
- N35S163U14BDA 1690mm - 1534lm Black
- N35S193U30BDA 1970mm - 1789lm White
- N35S193U02BDA 1970mm - 1789lm Anodized Grey
- N35S193U14BDA 1970mm - 1789lm Black
- N35S253U30BDA 2530mm - 2300lm White
- N35S253U02BDA 2530mm - 2300lm Anodized Grey
- N35S253U14BDA 2530mm - 2300lm Black
- N35S303U30BDA 3095mm - 2811lm White
- N35S303U02BDA 3095mm - 2811lm Anodized Grey
- N35S303U14BDA 3095mm - 2811lm Black
- N35SFC3U30BDA Flat Corner - 1022lm White
- N35SFC3U02BDA Flat Corner - 1022lm Anodized Grey
- N35SFC3U14BDA Flat Corner - 1022lm Black
- N35SDC3U30BDA Dihedral Corner - 1022lm White
- N35SDC3U02BDA Dihedral Corner - 1022lm Anodized Grey
- N35SDC3U14BDA Dihedral Corner - 1022lm Black
- N35SEM3U30BDA Emergency - 1278lm White
- N35SEM3U02BDA Emergency - 1278lm Anodized Grey
- N35SEM3U14BDA Emergency - 1278lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 35 Surface 3000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9050.40
- 08.9050.02
- 08.9050.NS
- 08.9050.06

Metal cover. Surface / Suspension Down. 35 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 35 Surface 3000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 35 Surface 3000K Micro-Prismatic Diffuser Dali designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N35S053U30BDA 565mm - 511lm White
- N35S053U02BDA 565mm - 511lm Anodized Grey
- N35S053U14BDA 565mm - 511lm Black
- N35S083U30BDA 845mm - 767lm White
- N35S083U02BDA 845mm - 767lm Anodized Grey
- N35S083U14BDA 845mm - 767lm Black
- N35S113U30BDA 1125mm - 1022lm White
- N35S113U02BDA 1125mm - 1022lm Anodized Grey
- N35S113U14BDA 1125mm - 1022lm Black
- N35S143U30BDA 1405mm - 1278lm White
- N35S143U02BDA 1405mm - 1278lm Anodized Grey
- N35S143U14BDA 1405mm - 1278lm Black
- N35S163U30BDA 1690mm - 1534lm White
- N35S163U02BDA 1690mm - 1534lm Anodized Grey
- N35S163U14BDA 1690mm - 1534lm Black
- N35S193U30BDA 1970mm - 1789lm White
- N35S193U02BDA 1970mm - 1789lm Anodized Grey
- N35S193U14BDA 1970mm - 1789lm Black
- N35S253U30BDA 2530mm - 2300lm White
- N35S253U02BDA 2530mm - 2300lm Anodized Grey
- N35S253U14BDA 2530mm - 2300lm Black
- N35S303U30BDA 3095mm - 2811lm White
- N35S303U02BDA 3095mm - 2811lm Anodized Grey
- N35S303U14BDA 3095mm - 2811lm Black
- N35SFC3U30BDA Flat Corner - 1022lm White
- N35SFC3U02BDA Flat Corner - 1022lm Anodized Grey
- N35SFC3U14BDA Flat Corner - 1022lm Black
- N35SDC3U30BDA Dihedral Corner - 1022lm White
- N35SDC3U02BDA Dihedral Corner - 1022lm Anodized Grey
- N35SDC3U14BDA Dihedral Corner - 1022lm Black
- N35SEM3U30BDA Emergency - 1278lm White
- N35SEM3U02BDA Emergency - 1278lm Anodized Grey
- N35SEM3U14BDA Emergency - 1278lm Black