


## IN-FINITY 35 SUSPENSION UP & DOWN 3000K MICRO-PRISMATIC DIFFUSER

<b>Number of heads</b>	1
<b>Mounting</b>	Pendant up & down
<b>Lamps description</b>	Top LED 32,6W/m 3000K CRI 80 1536 lm/m UP - 2558 lm/m DOWN
<b>Luminaire luminous flux</b>	See reference number
<b>Voltage (V)</b>	220/240
<b>Environment</b>	Indoor
<b>Notes</b>	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



**In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser**

designed by FLOS Architectural

### OPTICAL

<b>Aiming</b>	Fixed
<b>Light distribution symmetry</b>	Direct - Indirect
<b>Beam angle</b>	76°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### ELECTRICAL

<b>Transformer availability</b>	Included
<b>Transformer mounting</b>	Integral
<b>Transformer type</b>	Electronic
<b>Emergency</b>	Without
<b>Insulation class</b>	Class I

- N35U113U30B 1125mm - 1838lm White
- N35U113U02B 1125mm - 1838lm Anodized Grey
- N35U113U14B 1125mm - 1838lm Black
- N35U143U30B 1405mm - 2297lm White
- N35U143U02B 1405mm - 2297lm Anodized Grey
- N35U143U14B 1405mm - 2297lm Black
- N35U193U30B 1970mm - 3216lm White
- N35U193U02B 1970mm - 3216lm Anodized Grey
- N35U193U14B 1970mm - 3216lm Black
- N35U303U30B 3095mm - 5054lm White
- N35U303U02B 3095mm - 5054lm Anodized Grey
- N35U303U14B 3095mm - 5054lm Black
- N35UFC3U30B Flat Corner - 1838lm White
- N35UFC3U02B Flat Corner - 1838lm Anodized Grey
- N35UFC3U14B Flat Corner - 1838lm Black
- N35UEM3U30B Emergency - 2297lm White
- N35UEM3U02B Emergency - 2297lm Anodized Grey
- N35UEM3U14B Emergency - 2297lm Black
- N35U083U30B 845mm - 1378lm White
- N35U083U02B 845mm - 1378lm Anodized Grey
- N35U083U14B 845mm - 1378lm Black
- N35U163U30B 1690mm - 2757lm White
- N35U163U02B 1690mm - 2757lm Anodized Grey
- N35U163U14B 1690mm - 2757lm Black
- N35U253U30B 2530mm - 4135lm White
- N35U253U02B 2530mm - 4135lm Anodized Grey
- N35U253U14B 2530mm - 4135lm Black

### PHYSICAL

<b>Construction material</b>	Aluminium
------------------------------	-----------



## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories


### Structural



- 08.9056.40
- 08.9056.02
- 08.9056.NS
- 08.9056.06

#### Metal cover. Suspension Up & Down. 35 mm

Metal cover for the different profiles. 2 unit kit.



### In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U113U30B 1125mm - 1838lm White
- N35U113U02B 1125mm - 1838lm Anodized Grey
- N35U113U14B 1125mm - 1838lm Black
- N35U143U30B 1405mm - 2297lm White
- N35U143U02B 1405mm - 2297lm Anodized Grey
- N35U143U14B 1405mm - 2297lm Black
- N35U193U30B 1970mm - 3216lm White
- N35U193U02B 1970mm - 3216lm Anodized Grey
- N35U193U14B 1970mm - 3216lm Black
- N35U303U30B 3095mm - 5054lm White
- N35U303U02B 3095mm - 5054lm Anodized Grey
- N35U303U14B 3095mm - 5054lm Black
- N35UFC3U30B Flat Corner - 1838lm White
- N35UFC3U02B Flat Corner - 1838lm Anodized Grey
- N35UFC3U14B Flat Corner - 1838lm Black
- N35UEM3U30B Emergency - 2297lm White
- N35UEM3U02B Emergency - 2297lm Anodized Grey
- N35UEM3U14B Emergency - 2297lm Black
- N35U083U30B 845mm - 1378lm White
- N35U083U02B 845mm - 1378lm Anodized Grey
- N35U083U14B 845mm - 1378lm Black
- N35U163U30B 1690mm - 2757lm White
- N35U163U02B 1690mm - 2757lm Anodized Grey
- N35U163U14B 1690mm - 2757lm Black
- N35U253U30B 2530mm - 4135lm White
- N35U253U02B 2530mm - 4135lm Anodized Grey
- N35U253U14B 2530mm - 4135lm Black


### Mounting



- 08.0030

#### Suspension kit

One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



### In-Finity 35 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U113U30B 1125mm - 1838lm White
- N35U113U02B 1125mm - 1838lm Anodized Grey
- N35U113U14B 1125mm - 1838lm Black
- N35U143U30B 1405mm - 2297lm White
- N35U143U02B 1405mm - 2297lm Anodized Grey
- N35U143U14B 1405mm - 2297lm Black
- N35U193U30B 1970mm - 3216lm White
- N35U193U02B 1970mm - 3216lm Anodized Grey
- N35U193U14B 1970mm - 3216lm Black
- N35U303U30B 3095mm - 5054lm White
- N35U303U02B 3095mm - 5054lm Anodized Grey
- N35U303U14B 3095mm - 5054lm Black
- N35UFC3U30B Flat Corner - 1838lm White
- N35UFC3U02B Flat Corner - 1838lm Anodized Grey
- N35UFC3U14B Flat Corner - 1838lm Black
- N35UEM3U30B Emergency - 2297lm White
- N35UEM3U02B Emergency - 2297lm Anodized Grey
- N35UEM3U14B Emergency - 2297lm Black
- N35U083U30B 845mm - 1378lm White
- N35U083U02B 845mm - 1378lm Anodized Grey
- N35U083U14B 845mm - 1378lm Black
- N35U163U30B 1690mm - 2757lm White
- N35U163U02B 1690mm - 2757lm Anodized Grey
- N35U163U14B 1690mm - 2757lm Black
- N35U253U30B 2530mm - 4135lm White
- N35U253U02B 2530mm - 4135lm Anodized Grey
- N35U253U14B 2530mm - 4135lm Black

