


## IN-FINITY 35 SUSPENSION UP & DOWN 4000K GENERAL LIGHTING

|                                |  |
|--------------------------------|--|
| <b>Number of heads</b>         | 1  |
| <b>Mounting</b>                | Pendant up & down  |
| <b>Lamps description</b>       | Top LED 32,6W/m 4000K CRI 80 1680 lm/m UP - 2761 lm/m DOWN   |
| <b>Luminaire luminous flux</b> | See reference number   |
| <b>Voltage (V)</b>             | 220/240  |
| <b>Environment</b>             | Indoor   |
| <b>Notes</b>                   | Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps. |



**In-Finity 35 Suspension Up & Down 4000K General Lighting**  
designed by FLOS Architectural

### OPTICAL

|                                    |                   |
|------------------------------------|-------------------|
| <b>Aiming</b>                      | Fixed             |
| <b>Light distribution symmetry</b> | Direct - Indirect |
| <b>Beam angle</b>                  | 110°              |

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


### ELECTRICAL

|                                 |            |
|---------------------------------|------------|
| <b>Transformer availability</b> | Included   |
| <b>Transformer mounting</b>     | Integral   |
| <b>Transformer type</b>         | Electronic |
| <b>Emergency</b>                | Without    |
| <b>Insulation class</b>         | Class I    |

- N35U114G30B 1125mm - 2306lm **White**
- N35U114G02B 1125mm - 2306lm **Anodized Grey**
- N35U114G14B 1125mm - 2306lm **Black**
- N35U144G30B 1405mm - 2883lm **White**
- N35U144G02B 1405mm - 2883lm **Anodized Grey**
- N35U144G14B 1405mm - 2883lm **Black**
- N35U194G30B 1970mm - 4036lm **White**
- N35U194G02B 1970mm - 4036lm **Anodized Grey**
- N35U194G14B 1970mm - 4036lm **Black**
- N35U304G30B 3095mm - 6343lm **White**
- N35U304G02B 3095mm - 6343lm **Anodized Grey**
- N35U304G14B 3095mm - 6343lm **Black**
- N35UFC4G30B Flat Corner - 2306lm **White**
- N35UFC4G02B Flat Corner - 2306lm **Anodized Grey**
- N35UFC4G14B Flat Corner - 2306lm **Black**
- N35UEM4G30B Emergency - 2883lm **White**
- N35UEM4G02B Emergency - 2883lm **Anodized Grey**
- N35UEM4G14B Emergency - 2883lm **Black**
- N35U084G30B 845mm - 1730lm **White**
- N35U084G02B 845mm - 1730lm **Anodized Grey**
- N35U084G14B 845mm - 1730lm **Black**
- N35U164G30B 1690mm - 3460lm **White**
- N35U164G02B 1690mm - 3460lm **Anodized Grey**
- N35U164G14B 1690mm - 3460lm **Black**
- N35U254G30B 2530mm - 5189lm **White**
- N35U254G02B 2530mm - 5189lm **Anodized Grey**
- N35U254G14B 2530mm - 5189lm **Black**

### PHYSICAL

|                              |           |
|------------------------------|-----------|
| <b>Construction material</b> | Aluminium |
|------------------------------|-----------|



## In-Finity 35 Suspension Up & Down 4000K General Lighting . Accessories

### Structural



- 08.9056.40
- 08.9056.02
- 08.9056.NS
- 08.9056.06

#### Metal cover. Suspension Up & Down. 35 mm

Metal cover for the different profiles. 2 unit kit.


### Mounting



- 08.0030

#### Suspension kit


One unit Suspension kit (L = 4 m).  
Maximum distance between the suspension cables: 2 m.



### In-Finity 35 Suspension Up & Down 4000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U114G30B 1125mm - 2306lm White
- N35U114G02B 1125mm - 2306lm Anodized Grey
- N35U114G14B 1125mm - 2306lm Black
- N35U144G30B 1405mm - 2883lm White
- N35U144G02B 1405mm - 2883lm Anodized Grey
- N35U144G14B 1405mm - 2883lm Black
- N35U194G30B 1970mm - 4036lm White
- N35U194G02B 1970mm - 4036lm Anodized Grey
- N35U194G14B 1970mm - 4036lm Black
- N35U304G30B 3095mm - 6343lm White
- N35U304G02B 3095mm - 6343lm Anodized Grey
- N35U304G14B 3095mm - 6343lm Black
- N35UFC4G30B Flat Corner - 2306lm White
- N35UFC4G02B Flat Corner - 2306lm Anodized Grey
- N35UFC4G14B Flat Corner - 2306lm Black
- N35UEM4G30B Emergency - 2883lm White
- N35UEM4G02B Emergency - 2883lm Anodized Grey
- N35UEM4G14B Emergency - 2883lm Black
- N35U084G30B 845mm - 1730lm White
- N35U084G02B 845mm - 1730lm Anodized Grey
- N35U084G14B 845mm - 1730lm Black
- N35U164G30B 1690mm - 3460lm White
- N35U164G02B 1690mm - 3460lm Anodized Grey
- N35U164G14B 1690mm - 3460lm Black
- N35U254G30B 2530mm - 5189lm White
- N35U254G02B 2530mm - 5189lm Anodized Grey
- N35U254G14B 2530mm - 5189lm Black



## In-Finity 35 Suspension Up & Down 4000K General Lighting . Accessories

### Electrical



08.0031.00

#### Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

## In-Finity 35 Suspension Up & Down 4000K General Lighting . Lamps



#### Top LED

#### Lamp category:


LED

#### Socket:

Special base

#### Lamp type:

Top LED



## In-Finity 35 Suspension Up & Down 4000K General Lighting designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N35U114G30B 1125mm - 2306lm White
- N35U114G02B 1125mm - 2306lm Anodized Grey
- N35U114G14B 1125mm - 2306lm Black
- N35U144G30B 1405mm - 2883lm White
- N35U144G02B 1405mm - 2883lm Anodized Grey
- N35U144G14B 1405mm - 2883lm Black
- N35U194G30B 1970mm - 4036lm White
- N35U194G02B 1970mm - 4036lm Anodized Grey
- N35U194G14B 1970mm - 4036lm Black
- N35U304G30B 3095mm - 6343lm White
- N35U304G02B 3095mm - 6343lm Anodized Grey
- N35U304G14B 3095mm - 6343lm Black
- N35UFC4G30B Flat Corner - 2306lm White
- N35UFC4G02B Flat Corner - 2306lm Anodized Grey
- N35UFC4G14B Flat Corner - 2306lm Black
- N35UEM4G30B Emergency - 2883lm White
- N35UEM4G02B Emergency - 2883lm Anodized Grey
- N35UEM4G14B Emergency - 2883lm Black
- N35U084G30B 845mm - 1730lm White
- N35U084G02B 845mm - 1730lm Anodized Grey
- N35U084G14B 845mm - 1730lm Black
- N35U164G30B 1690mm - 3460lm White
- N35U164G02B 1690mm - 3460lm Anodized Grey
- N35U164G14B 1690mm - 3460lm Black
- N35U254G30B 2530mm - 5189lm White
- N35U254G02B 2530mm - 5189lm Anodized Grey
- N35U254G14B 2530mm - 5189lm Black

