


IN-FINITY 70 SUSPENSION DOWN 4000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Pendant
Lamps description	Top LED 23,1W/m 3091 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Down 4000K General Lighting Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	103°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N70D054G30BDA 565mm - 1367lm **White**
- N70D054G02BDA 565mm - 1367lm **Anodized Grey**
- N70D054G14BDA 565mm - 1367lm **Black**
- N70D084G30BDA 845mm - 2050lm **White**
- N70D084G02BDA 845mm - 2050lm **Anodized Grey**
- N70D084G14BDA 845mm - 2050lm **Black**
- N70D114G30BDA 1125mm - 2733lm **White**
- N70D114G02BDA 1125mm - 2733lm **Anodized Grey**
- N70D114G14BDA 1125mm - 2733lm **Black**
- N70D144G30BDA 1405mm - 3416lm **White**
- N70D144G02BDA 1405mm - 3416lm **Anodized Grey**
- N70D144G14BDA 1405mm - 3416lm **Black**
- N70D164G30BDA 1690mm - 4100lm **White**
- N70D164G02BDA 1690mm - 4100lm **Anodized Grey**
- N70D164G14BDA 1690mm - 4100lm **Black**
- N70D194G30BDA 1970mm - 4783lm **White**
- N70D194G02BDA 1970mm - 4783lm **Anodized Grey**
- N70D194G14BDA 1970mm - 4783lm **Black**
- N70D254G30BDA 2530mm - 6149lm **White**
- N70D254G02BDA 2530mm - 6149lm **Anodized Grey**
- N70D254G14BDA 2530mm - 6149lm **Black**
- N70D304G30BDA 3095mm - 7516lm **White**
- N70D304G02BDA 3095mm - 7516lm **Anodized Grey**
- N70D304G14BDA 3095mm - 7516lm **Black**
- N70DFC4G30BDA Flat Corner - 2733lm **White**
- N70DFC4G02BDA Flat Corner - 2733lm **Anodized Grey**
- N70DFC4G14BDA Flat Corner - 2733lm **Black**
- N70DEM4G30BDA Emergency - 3416lm **White**
- N70DEM4G02BDA Emergency - 3416lm **Anodized Grey**
- N70DEM4G14BDA Emergency - 3416lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 70 Suspension Down 4000K General Lighting Dali . Accessories

Structural



- 08.9052.40
- 08.9052.02
- 08.9052.NS
- 08.9052.06

Metal cover. Surface / Suspension Down. 70 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.



In-Finity 70 Suspension Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N70D054G30BDA 565mm - 1367lm **White**
- N70D054G02BDA 565mm - 1367lm **Anodized Grey**
- N70D054G14BDA 565mm - 1367lm **Black**
- N70D084G30BDA 845mm - 2050lm **White**
- N70D084G02BDA 845mm - 2050lm **Anodized Grey**
- N70D084G14BDA 845mm - 2050lm **Black**
- N70D114G30BDA 1125mm - 2733lm **White**
- N70D114G02BDA 1125mm - 2733lm **Anodized Grey**
- N70D114G14BDA 1125mm - 2733lm **Black**
- N70D144G30BDA 1405mm - 3416lm **White**
- N70D144G02BDA 1405mm - 3416lm **Anodized Grey**
- N70D144G14BDA 1405mm - 3416lm **Black**
- N70D164G30BDA 1690mm - 4100lm **White**
- N70D164G02BDA 1690mm - 4100lm **Anodized Grey**
- N70D164G14BDA 1690mm - 4100lm **Black**
- N70D194G30BDA 1970mm - 4783lm **White**
- N70D194G02BDA 1970mm - 4783lm **Anodized Grey**
- N70D194G14BDA 1970mm - 4783lm **Black**
- N70D254G30BDA 2530mm - 6149lm **White**
- N70D254G02BDA 2530mm - 6149lm **Anodized Grey**
- N70D254G14BDA 2530mm - 6149lm **Black**
- N70D304G30BDA 3095mm - 7516lm **White**
- N70D304G02BDA 3095mm - 7516lm **Anodized Grey**
- N70D304G14BDA 3095mm - 7516lm **Black**
- N70DFC4G30BDA Flat Corner - 2733lm **White**
- N70DFC4G02BDA Flat Corner - 2733lm **Anodized Grey**
- N70DFC4G14BDA Flat Corner - 2733lm **Black**
- N70DEM4G30BDA Emergency - 3416lm **White**
- N70DEM4G02BDA Emergency - 3416lm **Anodized Grey**
- N70DEM4G14BDA Emergency - 3416lm **Black**

In-Finity 70 Suspension Down 4000K General Lighting Dali . Accessories

Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 70 Suspension Down 4000K General Lighting Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Suspension Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit not included.

- N70D054G30BDA 565mm - 1367lm **White**
- N70D054G02BDA 565mm - 1367lm **Anodized Grey**
- N70D054G14BDA 565mm - 1367lm **Black**
- N70D084G30BDA 845mm - 2050lm **White**
- N70D084G02BDA 845mm - 2050lm **Anodized Grey**
- N70D084G14BDA 845mm - 2050lm **Black**
- N70D114G30BDA 1125mm - 2733lm **White**
- N70D114G02BDA 1125mm - 2733lm **Anodized Grey**
- N70D114G14BDA 1125mm - 2733lm **Black**
- N70D144G30BDA 1405mm - 3416lm **White**
- N70D144G02BDA 1405mm - 3416lm **Anodized Grey**
- N70D144G14BDA 1405mm - 3416lm **Black**
- N70D164G30BDA 1690mm - 4100lm **White**
- N70D164G02BDA 1690mm - 4100lm **Anodized Grey**
- N70D164G14BDA 1690mm - 4100lm **Black**
- N70D194G30BDA 1970mm - 4783lm **White**
- N70D194G02BDA 1970mm - 4783lm **Anodized Grey**
- N70D194G14BDA 1970mm - 4783lm **Black**
- N70D254G30BDA 2530mm - 6149lm **White**
- N70D254G02BDA 2530mm - 6149lm **Anodized Grey**
- N70D254G14BDA 2530mm - 6149lm **Black**
- N70D304G30BDA 3095mm - 7516lm **White**
- N70D304G02BDA 3095mm - 7516lm **Anodized Grey**
- N70D304G14BDA 3095mm - 7516lm **Black**
- N70DFC4G30BDA Flat Corner - 2733lm **White**
- N70DFC4G02BDA Flat Corner - 2733lm **Anodized Grey**
- N70DFC4G14BDA Flat Corner - 2733lm **Black**
- N70DEM4G30BDA Emergency - 3416lm **White**
- N70DEM4G02BDA Emergency - 3416lm **Anodized Grey**
- N70DEM4G14BDA Emergency - 3416lm **Black**