


IN-FINITY 70 SURFACE 4000K MICRO-PRISMATIC DIFFUSER DALI

Number of heads	1
Mounting	Surface
Lamps description	Top LED 23,1W/m 3091 lm/m 4000K CRI 80
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Surface 4000K Micro-Prismatic Diffuser Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	72°

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N70S054U30BDA 565mm - 818lm White
- N70S054U02BDA 565mm - 818lm Anodized Grey
- N70S054U14BDA 565mm - 818lm Black
- N70S084U30BDA 845mm - 1227lm White
- N70S084U02BDA 845mm - 1227lm Anodized Grey
- N70S084U14BDA 845mm - 1227lm Black
- N70S114U30BDA 1125mm - 1636lm White
- N70S114U02BDA 1125mm - 1636lm Anodized Grey
- N70S114U14BDA 1125mm - 1636lm Black
- N70S144U30BDA 1405mm - 2045lm White
- N70S144U02BDA 1405mm - 2045lm Anodized Grey
- N70S144U14BDA 1405mm - 2045lm Black
- N70S164U30BDA 1690mm - 2454lm White
- N70S164U02BDA 1690mm - 2454lm Anodized Grey
- N70S164U14BDA 1690mm - 2454lm Black
- N70S194U30BDA 1970mm - 2862lm White
- N70S194U02BDA 1970mm - 2862lm Anodized Grey
- N70S194U14BDA 1970mm - 2862lm Black
- N70S254U30BDA 2530mm - 3680lm White
- N70S254U02BDA 2530mm - 3680lm Anodized Grey
- N70S254U14BDA 2530mm - 3680lm Black
- N70S304U30BDA 3095mm - 4498lm White
- N70S304U02BDA 3095mm - 4498lm Anodized Grey
- N70S304U14BDA 3095mm - 4498lm Black
- N70SFC4U30BDA Flat Corner - 1636lm White
- N70SFC4U02BDA Flat Corner - 1636lm Anodized Grey
- N70SFC4U14BDA Flat Corner - 1636lm Black
- N70SDC4U30BDA Dihedral Corner - 1636lm White
- N70SDC4U02BDA Dihedral Corner - 1636lm Anodized Grey
- N70SDC4U14BDA Dihedral Corner - 1636lm Black
- N70SEM4U30BDA Emergency - 2045lm White
- N70SEM4U02BDA Emergency - 2045lm Anodized Grey
- N70SEM4U14BDA Emergency - 2045lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 70 Surface 4000K Micro-Prismatic Diffuser Dali . Accessories

Structural



- 08.9052.40
- 08.9052.02
- 08.9052.NS
- 08.9052.06

Metal cover. Surface / Suspension Down. 70 mm

Metal cover for the different profiles. 2 unit kit.

In-Finity 70 Surface 4000K Micro-Prismatic Diffuser Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Surface 4000K Micro-Prismatic Diffuser Dali designed by FLOS Architectural

LED modular system for surface installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

- N70S054U30BDA 565mm - 818lm White
- N70S054U02BDA 565mm - 818lm Anodized Grey
- N70S054U14BDA 565mm - 818lm Black
- N70S084U30BDA 845mm - 1227lm White
- N70S084U02BDA 845mm - 1227lm Anodized Grey
- N70S084U14BDA 845mm - 1227lm Black
- N70S114U30BDA 1125mm - 1636lm White
- N70S114U02BDA 1125mm - 1636lm Anodized Grey
- N70S114U14BDA 1125mm - 1636lm Black
- N70S144U30BDA 1405mm - 2045lm White
- N70S144U02BDA 1405mm - 2045lm Anodized Grey
- N70S144U14BDA 1405mm - 2045lm Black
- N70S164U30BDA 1690mm - 2454lm White
- N70S164U02BDA 1690mm - 2454lm Anodized Grey
- N70S164U14BDA 1690mm - 2454lm Black
- N70S194U30BDA 1970mm - 2862lm White
- N70S194U02BDA 1970mm - 2862lm Anodized Grey
- N70S194U14BDA 1970mm - 2862lm Black
- N70S254U30BDA 2530mm - 3680lm White
- N70S254U02BDA 2530mm - 3680lm Anodized Grey
- N70S254U14BDA 2530mm - 3680lm Black
- N70S304U30BDA 3095mm - 4498lm White
- N70S304U02BDA 3095mm - 4498lm Anodized Grey
- N70S304U14BDA 3095mm - 4498lm Black
- N70SFC4U30BDA Flat Corner - 1636lm White
- N70SFC4U02BDA Flat Corner - 1636lm Anodized Grey
- N70SFC4U14BDA Flat Corner - 1636lm Black
- N70SDC4U30BDA Dihedral Corner - 1636lm White
- N70SDC4U02BDA Dihedral Corner - 1636lm Anodized Grey
- N70SDC4U14BDA Dihedral Corner - 1636lm Black
- N70SEM4U30BDA Emergency - 2045lm White
- N70SEM4U02BDA Emergency - 2045lm Anodized Grey
- N70SEM4U14BDA Emergency - 2045lm Black