# FLOS

## IN-FINITY 70 RECESSED TRIM 4000K GENERAL LIGHTING

Number of heads Mounting Lamps description Luminaire luminous flux Voltage (V) Environment Notes I Recessed Trim Top LED 23, I W/m 3091 lm/m 4000K CRI 80 See reference number 220/240 Indoor Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

### OPTICAL

| Aiming                      | Fixed     |
|-----------------------------|-----------|
| Light distribution symmetry | Symmetric |
| Beam angle                  | 103°      |

#### ELECTRICAL

| Transformer availability |  |
|--------------------------|--|
| Transformer mounting     |  |
| Transformer type         |  |
| Emergency                |  |
| Insulation class         |  |

## PHYSICAL

Recessed depth (mm) Construction material 135 Aluminium

Included Integral Electronic Without Class I





### In-Finity 70 Recessed Trim 4000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

| N70T054G30B 565mm - 1367lm White               |
|--|
| N70T054G02B 565mm - 1367lm Anodized Grey       |
| N70T054G14B 565mm - 1367lm Black               |
| N70T084G30B 845mm - 2050lm White               |
| N70T084G02B 845mm - 2050lm Anodized Grey       |
| N70T084G14B 845mm - 2050lm Black               |
| N70T114G30B 1125mm - 2733lm White              |
| N70T114G02B 1125mm - 2733lm Anodized Grey      |
| N70T114G14B 1125mm - 2733lm Black              |
| N70T144G30B 1405mm - 3416lm White              |
| N70T144G02B 1405mm - 3416lm Anodized Grey      |
| N70T144G14B 1405mm - 3416lm Black              |
| N70T164G30B 1690mm - 4100lm White              |
| N70T164G02B 1690mm - 41001m Anodized Grey      |
| N70T164G14B 1690mm - 41001m Black              |
| N70T194G30B 1970mm - 4783lm White              |
| N70T194G02B 1970mm - 47831m Anodized Grey      |
| N70T194G14B 1970mm - 47831m Black              |
| N70T254G30B 2530mm - 6149lm White              |
| N70T254G02B 2530mm - 6149Im Anodized Grey      |
| N70T254G14B 2530mm - 61491m Black              |
| N70T304G30B 3095mm - 7516lm White              |
| N70T304G02B 3095mm - 7516lm Anodized Grey      |
| N70T304G14B 3095mm - 7516lm Black              |
| N70TFC4G30B Flat Corner - 2733lm White         |
| N70TFC4G02B Flat Corner - 2733lm Anodized Grey |
| N70TFC4G14B Flat Corner - 2733Im Black         |
| N70TDC4G30B Dihedral Corner - White            |
| N70TDC4G02B Dihedral Corner - Anodized Grey    |
| N70TDC4G14B Dihedral Corner - Black            |
| N70TEM4G30B Emergency - 3416lm White           |
| N70TEM4G02B Emergency - 3416Im Anodized Grey   |
| N70TEM4G14B Emergency - 3416Im Black           |

# FLOS

### In-Finity 70 Recessed Trim 4000K General Lighting . Accessories

#### Structural



5

Metal cover. Recessed Trim. 70 mm Metal cover for the different profiles. 2 unit kit.

#### In-Finity 70 Recessed Trim 4000K General Lighting . Lamps



Top LED Lamp category: LED Socket: Special base Lamp type: Top LED



In-Finity 70 Recessed Trim 4000K General Lighting

designed by FLOS Architectural

LED modular system for recessed Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

| N70T054G30B 565mm - 1367lm White               |
|--|
| N70T054G02B 565mm - 1367lm Anodized Grey       |
| N70T054G14B 565mm - 1367Im Black               |
| N70T084G30B 845mm - 2050lm White               |
| N70T084G02B 845mm - 2050lm Anodized Grey       |
| N70T084G14B 845mm - 2050lm Black               |
| N70T114G30B 1125mm - 2733lm White              |
| N70T114G02B 1125mm - 2733lm Anodized Grey      |
| N70T114G14B 1125mm - 2733lm Black              |
| N70T144G30B 1405mm - 3416lm White              |
| N70T144G02B 1405mm - 3416lm Anodized Grey      |
| N70T144G14B 1405mm - 3416lm Black              |
| N70T164G30B 1690mm - 4100lm White              |
| N70T164G02B 1690mm - 4100lm Anodized Grey      |
| N70T164G14B 1690mm - 41001m Black              |
| N70T194G30B 1970mm - 4783lm White              |
| N70T194G02B 1970mm - 4783Im Anodized Grey      |
| N70T194G14B 1970mm - 4783Im Black              |
| N70T254G30B 2530mm - 6149Im White              |
| N70T254G02B 2530mm - 6149Im Anodized Grey      |
| N70T254G14B 2530mm - 61491m Black              |
| N70T304G30B 3095mm - 7516lm White              |
| N70T304G02B 3095mm - 7516lm Anodized Grey      |
| N70T304G14B 3095mm - 7516lm Black              |
| N70TFC4G30B Flat Corner - 2733lm White         |
| N70TFC4G02B Flat Corner - 2733Im Anodized Grey |
| N70TFC4G14B Flat Corner - 2733Im Black         |
| N70TDC4G30B Dihedral Corner - White            |
| N70TDC4G02B Dihedral Corner - Anodized Grey    |
| N70TDC4G14B Dihedral Corner - Black            |
| N70TEM4G30B Emergency - 3416lm White           |
| N70TEM4G02B Emergency - 3416Im Anodized Grey   |
| N70TEM4G14B Emergency - 3416lm Black           |

www.flos.com