


IN-FINITY 70 SUSPENSION UP & DOWN 3000K MICRO-PRISMATIC DIFFUSER

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 35,9W/m 3000K CRI 80 1536 lm/m UP - 2877 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	72°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic
Emergency	Without
Insulation class	Class I

- N70U113U30B 1125mm - 2807lm White
- N70U113U02B 1125mm - 2807lm Anodized Grey
- N70U113U14B 1125mm - 2807lm Black
- N70U143U30B 1405mm - 3508lm White
- N70U143U02B 1405mm - 3508lm Anodized Grey
- N70U143U14B 1405mm - 3508lm Black
- N70U193U30B 1970mm - 4911lm White
- N70U193U02B 1970mm - 4911lm Anodized Grey
- N70U193U14B 1970mm - 4911lm Black
- N70U303U30B 3095mm - 7718lm White
- N70U303U02B 3095mm - 7718lm Anodized Grey
- N70U303U14B 3095mm - 7718lm Black
- N70UFC3U30B Flat Corner - 2807lm White
- N70UFC3U02B Flat Corner - 2807lm Anodized Grey
- N70UFC3U14B Flat Corner - 2807lm Black
- N70UEM3U30B Emergency - 3508lm White
- N70UEM3U02B Emergency - 3508lm Anodized Grey
- N70UEM3U14B Emergency - 3508lm Black
- N70U083U30B 845mm - 2105lm White
- N70U083U02B 845mm - 2105lm Anodized Grey
- N70U083U14B 845mm - 2105lm Black
- N70U163U30B 1690mm - 4210lm White
- N70U163U02B 1690mm - 4210lm Anodized Grey
- N70U163U14B 1690mm - 4210lm Black
- N70U253U30B 2530mm - 6315lm White
- N70U253U02B 2530mm - 6315lm Anodized Grey
- N70U253U14B 2530mm - 6315lm Black

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories


Structural



- 08.9057.40
- 08.9057.02
- 08.9057.NS
- 08.9057.06

Metal cover. Suspension Up & Down. 70 mm

Metal cover for the different profiles. 2 unit kit.



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U113U30B 1125mm - 2807lm White
- N70U113U02B 1125mm - 2807lm Anodized Grey
- N70U113U14B 1125mm - 2807lm Black
- N70U143U30B 1405mm - 3508lm White
- N70U143U02B 1405mm - 3508lm Anodized Grey
- N70U143U14B 1405mm - 3508lm Black
- N70U193U30B 1970mm - 4911lm White
- N70U193U02B 1970mm - 4911lm Anodized Grey
- N70U193U14B 1970mm - 4911lm Black
- N70U303U30B 3095mm - 7718lm White
- N70U303U02B 3095mm - 7718lm Anodized Grey
- N70U303U14B 3095mm - 7718lm Black
- N70UFC3U30B Flat Corner - 2807lm White
- N70UFC3U02B Flat Corner - 2807lm Anodized Grey
- N70UFC3U14B Flat Corner - 2807lm Black
- N70UEM3U30B Emergency - 3508lm White
- N70UEM3U02B Emergency - 3508lm Anodized Grey
- N70UEM3U14B Emergency - 3508lm Black
- N70U083U30B 845mm - 2105lm White
- N70U083U02B 845mm - 2105lm Anodized Grey
- N70U083U14B 845mm - 2105lm Black
- N70U163U30B 1690mm - 4210lm White
- N70U163U02B 1690mm - 4210lm Anodized Grey
- N70U163U14B 1690mm - 4210lm Black
- N70U253U30B 2530mm - 6315lm White
- N70U253U02B 2530mm - 6315lm Anodized Grey
- N70U253U14B 2530mm - 6315lm Black


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m). Maximum distance between the suspension cables: 2 m.



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Accessories

Electrical



08.0031.00

Power supply rose

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Suspension Up & Down 3000K Micro-Prismatic Diffuser

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U113U30B 1125mm - 2807lm White
- N70U113U02B 1125mm - 2807lm Anodized Grey
- N70U113U14B 1125mm - 2807lm Black
- N70U143U30B 1405mm - 3508lm White
- N70U143U02B 1405mm - 3508lm Anodized Grey
- N70U143U14B 1405mm - 3508lm Black
- N70U193U30B 1970mm - 4911lm White
- N70U193U02B 1970mm - 4911lm Anodized Grey
- N70U193U14B 1970mm - 4911lm Black
- N70U303U30B 3095mm - 7718lm White
- N70U303U02B 3095mm - 7718lm Anodized Grey
- N70U303U14B 3095mm - 7718lm Black
- N70UFC3U30B Flat Corner - 2807lm White
- N70UFC3U02B Flat Corner - 2807lm Anodized Grey
- N70UFC3U14B Flat Corner - 2807lm Black
- N70UEM3U30B Emergency - 3508lm White
- N70UEM3U02B Emergency - 3508lm Anodized Grey
- N70UEM3U14B Emergency - 3508lm Black
- N70U083U30B 845mm - 2105lm White
- N70U083U02B 845mm - 2105lm Anodized Grey
- N70U083U14B 845mm - 2105lm Black
- N70U163U30B 1690mm - 4210lm White
- N70U163U02B 1690mm - 4210lm Anodized Grey
- N70U163U14B 1690mm - 4210lm Black
- N70U253U30B 2530mm - 6315lm White
- N70U253U02B 2530mm - 6315lm Anodized Grey
- N70U253U14B 2530mm - 6315lm Black

