


IN-FINITY 70 SUSPENSION UP & DOWN 4000K GENERAL LIGHTING DALI

Number of heads	1
Mounting	Pendant up & down
Lamps description	Top LED 35,9W/m 4000K CRI 80 1680 lm/m UP - 3091 lm/m DOWN
Luminaire luminous flux	See reference number
Voltage (V)	220/240
Environment	Indoor
Notes	Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1400 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down 4000K General Lighting Dali
designed by FLOS Architectural

OPTICAL

Aiming	Fixed
Light distribution symmetry	Direct - Indirect
Beam angle	103°

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.


ELECTRICAL

Transformer availability	Included
Transformer mounting	Integral
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class I

- N70U114G30BDA 1125mm - 4137lm **White**
- N70U114G02BDA 1125mm - 4137lm **Anodized Grey**
- N70U114G14BDA 1125mm - 4137lm **Black**
- N70U144G30BDA 1405mm - 5171lm **White**
- N70U144G02BDA 1405mm - 5171lm **Anodized Grey**
- N70U144G14BDA 1405mm - 5171lm **Black**
- N70U194G30BDA 1970mm - 7240lm **White**
- N70U194G02BDA 1970mm - 7240lm **Anodized Grey**
- N70U194G14BDA 1970mm - 7240lm **Black**
- N70U304G30BDA 3095mm - 11377lm **White**
- N70U304G02BDA 3095mm - 11377lm **Anodized Grey**
- N70U304G14BDA 3095mm - 11377lm **Black**
- N70UFC4G30BDA Flat Corner - 4137lm **White**
- N70UFC4G02BDA Flat Corner - 4137lm **Anodized Grey**
- N70UFC4G14BDA Flat Corner - 4137lm **Black**
- N70UEM4G30BDA Emergency - 5171lm **White**
- N70UEM4G02BDA Emergency - 5171lm **Anodized Grey**
- N70UEM4G14BDA Emergency - 5171lm **Black**
- N70U084G30BDA 845mm - 3103lm **White**
- N70U084G02BDA 845mm - 3103lm **Anodized Grey**
- N70U084G14BDA 845mm - 3103lm **Black**
- N70U164G30BDA 1690mm - 6205lm **White**
- N70U164G02BDA 1690mm - 6205lm **Anodized Grey**
- N70U164G14BDA 1690mm - 6205lm **Black**
- N70U254G30BDA 2530mm - 9308lm **White**
- N70U254G02BDA 2530mm - 9308lm **Anodized Grey**
- N70U254G14BDA 2530mm - 9308lm **Black**

PHYSICAL

Construction material	Aluminium
------------------------------	-----------



In-Finity 70 Suspension Up & Down 4000K General Lighting Dali . Accessories

Structural



- 08.9057.40
- 08.9057.02
- 08.9057.NS
- 08.9057.06

Metal cover. Suspension Up & Down. 70 mm

Metal cover for the different profiles. 2 unit kit.


Mounting



- 08.0030

Suspension kit

One unit Suspension kit (L = 4 m).
Maximum distance between the suspension cables: 2 m.




In-Finity 70 Suspension Up & Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U114G30BDA 1125mm - 4137lm White
- N70U114G02BDA 1125mm - 4137lm Anodized Grey
- N70U114G14BDA 1125mm - 4137lm Black
- N70U144G30BDA 1405mm - 5171lm White
- N70U144G02BDA 1405mm - 5171lm Anodized Grey
- N70U144G14BDA 1405mm - 5171lm Black
- N70U194G30BDA 1970mm - 7240lm White
- N70U194G02BDA 1970mm - 7240lm Anodized Grey
- N70U194G14BDA 1970mm - 7240lm Black
- N70U304G30BDA 3095mm - 11377lm White
- N70U304G02BDA 3095mm - 11377lm Anodized Grey
- N70U304G14BDA 3095mm - 11377lm Black
- N70UFC4G30BDA Flat Corner - 4137lm White
- N70UFC4G02BDA Flat Corner - 4137lm Anodized Grey
- N70UFC4G14BDA Flat Corner - 4137lm Black
- N70UEM4G30BDA Emergency - 5171lm White
- N70UEM4G02BDA Emergency - 5171lm Anodized Grey
- N70UEM4G14BDA Emergency - 5171lm Black
- N70U084G30BDA 845mm - 3103lm White
- N70U084G02BDA 845mm - 3103lm Anodized Grey
- N70U084G14BDA 845mm - 3103lm Black
- N70U164G30BDA 1690mm - 6205lm White
- N70U164G02BDA 1690mm - 6205lm Anodized Grey
- N70U164G14BDA 1690mm - 6205lm Black
- N70U254G30BDA 2530mm - 9308lm White
- N70U254G02BDA 2530mm - 9308lm Anodized Grey
- N70U254G14BDA 2530mm - 9308lm Black



In-Finity 70 Suspension Up & Down 4000K General Lighting Dali . Accessories

Electrical



08.0031.00.DA

Power supply rose. Dali

Power supply rose for the hanging installation of the In-finity. The standard version comes with a three-pole cable for basic switching. The Dali version comes with a five-pole cable that can be used for double switching, independent from the direct and indirect lighting in the standard Up&Down version. Includes a 4 m suspension cable

In-Finity 70 Suspension Up & Down 4000K General Lighting Dali . Lamps



Top LED

Lamp category:


LED

Socket:

Special base

Lamp type:

Top LED



In-Finity 70 Suspension Up & Down 4000K General Lighting Dali

designed by FLOS Architectural

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

- N70U114G30BDA 1125mm - 4137lm White
- N70U114G02BDA 1125mm - 4137lm Anodized Grey
- N70U114G14BDA 1125mm - 4137lm Black
- N70U144G30BDA 1405mm - 5171lm White
- N70U144G02BDA 1405mm - 5171lm Anodized Grey
- N70U144G14BDA 1405mm - 5171lm Black
- N70U194G30BDA 1970mm - 7240lm White
- N70U194G02BDA 1970mm - 7240lm Anodized Grey
- N70U194G14BDA 1970mm - 7240lm Black
- N70U304G30BDA 3095mm - 11377lm White
- N70U304G02BDA 3095mm - 11377lm Anodized Grey
- N70U304G14BDA 3095mm - 11377lm Black
- N70UFC4G30BDA Flat Corner - 4137lm White
- N70UFC4G02BDA Flat Corner - 4137lm Anodized Grey
- N70UFC4G14BDA Flat Corner - 4137lm Black
- N70UEM4G30BDA Emergency - 5171lm White
- N70UEM4G02BDA Emergency - 5171lm Anodized Grey
- N70UEM4G14BDA Emergency - 5171lm Black
- N70U084G30BDA 845mm - 3103lm White
- N70U084G02BDA 845mm - 3103lm Anodized Grey
- N70U084G14BDA 845mm - 3103lm Black
- N70U164G30BDA 1690mm - 6205lm White
- N70U164G02BDA 1690mm - 6205lm Anodized Grey
- N70U164G14BDA 1690mm - 6205lm Black
- N70U254G30BDA 2530mm - 9308lm White
- N70U254G02BDA 2530mm - 9308lm Anodized Grey
- N70U254G14BDA 2530mm - 9308lm Black

