

SOFT PLATE IL + JUNCO 400 MM

Mounting Junco 400 mm 3000K

Lamps description Power LED DC 700 mA 2,1W 216 lm 3000K CRI 80

Environment Indoor

Notes Pre-wired product to be connected to constant current.

Recommended power supply: 60.8655.



Transformer availability

Separate item

Remote

Remergency

Insulation class

Separate item

Remote

Class III



Length (mm) 200 **Width (mm)** 200

Weight (kg) Soft Plate: 0,70 / Junco: 0,19





Soft Plate IL + Junco 400 mm designed by FLOS Soft Architecture

Semi-recessed LED luminaire for indoor applications. Seamless integration in the architectural environment by Soft Architecture technology. Power supply not included.

SA.5200.5.120 Soft Plate White

08.8591.40A Junco 400 mm 3000K White

08.8591.06A Junco 400 mm 3000K Chrome

08.8591.AAA Junco 400 mm 3000K Black






CERTIFICATIONS









info@flos.it www.flos.com



Soft Plate IL + Junco 400 mm . Accessories

Power Supply





60.8655

Not dimmable continuous current power supply of 17W Not dimmable continuous current power supply of 17W, 700mA - 100/240V - 50/60Hz.

60.8533

Continuous current power supply of 25W

Continuous current power supply of 25W, 120-240V -50/60Hz with power current selected through adjustable 350/ 500/700mA I-10V switch or push dimming.



Soft Plate IL + Junco 400 mm designed by FLOS Soft Architecture

Semi-recessed LED luminaire for indoor applications. Seamless integration in the architectural environment by Soft Architecture technology. Power supply not included.

SA.5200.5.120 Soft Plate White 08.8591.40A Junco 400 mm 3000K White 08.8591.06A Junco 400 mm 3000K Chrome 08.8591.AAA Junco 400 mm 3000K Black




CERTIFICATIONS









info@flos.it www.flos.com