
SPIGOLO FLOOR

Studiocharlie

Floor, wall/ceiling, pendant and table lamps based on an extruded and tubular aluminium structure, connected with moulded polymer joints, with white or black painted finish. Thanks to the joints, enabling the profiles to house LED sources, one can rotate 360° in order to produce a directional direct or indirect lighting, screened by an opaline diffuser in polycarbonate. The floor version is designed as such to provide a virtual divider to ambiences, while the ceiling and wall versions allow the enlightenment of the ambience in a versatile and a comfortable way. LED sources are dimmable.





LED 2700K

LAMPING

Source3xlinear LEDTotal power6+10+33WEmissiontriple, diffused

Switching mono switch, dimmable

Tension 110/240V Color temperature 2700K

Luminous flux 335lm+600lm+1765lm

Typ CRI 85 Energy class A+

Materials aluminium + PC + ABS

Notes orientable diffusers, dimmer on cable, cable length 4,5m

Net lamp weight 10 kg

Codes Structure


SPI LW2 23 white SPI LN2 23 black

PACKAGE

Package 01 Dimension: 57x78x16 cm / Gross weight: 6,5 kg
Package 02 Dimension: 18 x22x190 cm / Gross weight: 7 kg

Certificazioni

C € ERI ĽK



LED 3000K

LAMPING

Source3xlinear LEDTotal power6+10+33WEmissiontriple, diffused

Switching mono switch, dimmable

Tension 110/240V Color temperature 3000K

Luminous flux 335lm+600lm+1765lm

Typ CRI 85 Energy class A+

Materials aluminium + PC + ABS

Notes orientable diffusers, dimmer on cable, cable length 4,5m

Net lamp weight 10 kg

Codes Structure

SPI LWW 23 white SPI LNN 23 black

PACKAGE

Package 01 Dimension: 57x78x16 cm / Gross weight: 6,5 kg
Package 02 Dimension: 18 x22x190 cm / Gross weight: 7 kg

Certificazioni

C € ERI ĽK

