


TECHNICAL DATA SHEET ART. S.4665N - STEP BOLLARD

Version is available on request




1 MODULES LED 4000K 230V 151lm 2.1W CRI 90

Rated luminaire luminous flux: 17lm

Rated input power: 3W

Luminaire efficacy: 6lm/W

Electronic ballast 220÷240V 50/60Hz



* Photometric measured using WHITE LED 3000K



PRODUCT TYPE

Bollard fitting. IP rating IP 65

MATERIAL CHARACTERISTICS

Aluminium die cast housing in EN AB-47100 (low copper content) and extruded EN AW-6060 with high resistance against corrosion. Stone wash surface treatment prior to painting process. A4 grade Stainless Steel screws with 2,5-3% molybdenum content which increases the resistance against corrosion. Silicone gaskets. Painting Process : 3 Step Process

1) Surface treatment with BONDERITE. A heavy metal free chemical surface treatment containing ceramic nano particles giving a cohesive, inorganic and highly dense protective coating. 2) PRE POLYMERIZATION a process of introducing an epoxy primer with excellent characteristics to the paint which also offers very high resistance to oxidation due to its Zinc content. 3) POLYMERIZATION a process with the application of polyester powder with high resistance against UV rays and harsh weather conditions. Resistance test protection for Marine applications for 1200h. Mechanical resistance IK 06

LIGHTING PERFORMANCE

Reflector in plastic material white painted. Transparent toughened glass 4 mm thick. LOR -- The upper part of the luminaire has a grid that works as a radiator, in order to dissipate the heat produced by the LED positioned underneath.

INSTALLATION AND MAINTENANCE

The housing is totally extractible through a spring mechanism; this makes the installation and maintenance easier but more suitable for those areas that are not exposed to potential vandalism.

WIRING

Supply 0.5m cable section type H07RN-F . The 230V - 700mA electronic ballast is housed inside the luminaire. Isolation: CLASS I . Available colours: Aluminium grey (cod.14). Weight: 1.9 Kg Glow Wire test: 850°C

L.E.D circuit included.

STEP REGISTERED DESIGN

This luminaire contains built-in LED modules with energy class: A, A+, A++. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user (Regulation UE 874/2012).

LED circuit boards are engineered accordingly to actual Lumen Maintenance regulation (LM80) and Technical Memorandum (TM21) where uniformity and quality of light is 50.000 hours referred to L70 B20 Ta 25°C.

Lifecycle refers to LED circuit boards only, all others components of the luminaire are excluded.

TECHNICAL DATA SHEET ART. S.4665N - STEP BOLLARD ACCESSORIES



S.4663

FLANGE FOR GROUND APPLICATION BOLLARD

Flange 77mm x 58mm h 170mm to be fixed in concrete with stainless steel screws for fixing in the ground. Footstall dimension can be calculated according to your country norms and ground properties.