



PARRI emergency exit sign

big, ceiling/wall, white

| | |
|---------------------------|--------------------------------|
| Article number | 1000295 |
| Feed-in capability | No |
| Lamp included | No |
| Width | 33 cm |
| Height | 25 cm |
| Depth | 6 cm |
| Net weight | 1.458 kg |
| Gross weight | 1.646 kg |
| Voltage | 220-240V ~50/60Hz |
| Protection class | II |
| Average lifespan | 25000 Hours |
| Colour temperature | 4000 Kelvin |
| Colour rendering index | 70 |
| Luminous flux | 32 lm |
| Energy efficiency class | A++ |
| Way of mounting | Surface mounted / Wall mounted |
| Colour | white |
| Form | square |
| Light distribution type 1 | diffuse |
| Material | ABS/plastic PC |

Articles of this series

240002 P-LIGHT 33, wall and ceiling light, emergency exit light, LED, 6000K, white, L/W/H 33/6/25 cm, 4W

The PARRI3 emergency lighting system is suitable for use as a wall and ceiling light. The safety lights are fitted with a built-in Ni-MH battery with an automatic self-test. The detection range is 24 m. The emergency operating time of the luminaires is three hours. The luminaires can be operated permanently switched on / stand-by operation. The luminaire is connected directly to the 230V mains supply. Other variants of the PARRI series are available. The luminaire is supplied with three signs with different arrow directions (right / left / down). As an option, other signs are available.

Notes
