





KAMUELA

fire protection recessed ceiling light, LED, 3000K, black, 38°, IP65

| | |
|---------------------------|-------------------------------------|
| Article number | 1001011 |
| Feed-in capability | No |
| Lamp included | No |
| Installation diameter | 7 cm |
| Installation depth | 10.2 cm |
| Height | 10.2 cm |
| Diameter | 8.8 cm |
| Net weight | 0.268 kg |
| Gross weight | 0.322 kg |
| Voltage | 220-240V ~50Hz |
| Max. wattage | 8 Watt |
| Protection class | II |
| IP-rating | IP 65 |
| Beam angle | 38 Degree |
| Average lifespan | 35000 Hours |
| Colour temperature | 3000 Kelvin |
| Colour rendering index | 80 |
| Luminous flux | 600 lm |
| Energy efficiency class | A++ |
| Way of mounting | Recessed mounted / Ceiling recessed |
| Colour | black |
| Form | round |
| Light distribution type 1 | direct |
| Light distribution type 2 | rotational symmetric |
| Material | Aluminium |

The KAMUEL LED recessed fitting is equipped with an integrated premium LED. The recessed light is made of aluminium and plastic and is fitted with a warm-white LED. The fire-resistant recessed fitting series is fire-resistant for at least 90 minutes. An appropriate dimmable constant current driver is integrated for operating the recessed fitting, and is therefore suitable for direct connection to 230 Volts. This luminaire contains built-in LED lamps and is available with different housing colours. EEL: A - A++. The lamps in the luminaire cannot be replaced.

Notes
