




## L-LINE OUT WL

## Outdoor LED wall-mounted light anthracite CCT switch 3000/4000K

With its linear light variety, the L-LINE OUT family lights the way outdoors. Despite their individual differences, the individual members speak a common language of form, encapsulated in the clean lines of the letter "L". As far as lighting technology is concerned, there are no compromises: the CCT switch for easy selection of light colour temperature (3000 or 4000K) prior to installation), the straightforward installation process, and a protection rating of IP 65 are just some of the features that make the L-LINE OUT surface-mounted wall light a winner.



## **TECHNICAL DATA**

Item no.:	1003539
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350 mA/V
Width	15.0 cm
Height	10.0 cm
Depth	10.0 cm
Net weight	1.024 kg
Gross weight	1.237 kg
IP Code	IP 65
Safety class	1
Impact resistance class	IK02
Impact resistance	0,2000000000000001 Joule
Assembly	Surface
Assembly details	Wall
Number of through-wires	10
Wattage	7 W
Lumen	500 / 570 lm
Colour temperature	3000/4000 Kelvin
Color	anthracite
CRI	>80
Binning	6



LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
BIG WHITE Page	688

Notes