







## **F-LIGHT** recessed fitting

LED, 3000K, round, white, 40°, rigid, 6.35W

| Article number            | 114051                           |
|---------------------------|----------------------------------|
| Max. wattage              | 6.35 Watt                        |
| Light distribution type 1 | Direct                           |
| Feed-in capability        | No                               |
| Lamp included             | No                               |
| Height                    | 5 cm                             |
| Diameter                  | 8 cm                             |
| Net weight                | 0.202 kg                         |
| Gross weight              | 0.235 kg                         |
| Voltage                   | 350 Volts                        |
| Protection class          | III                              |
| Beam angle                | 40 Degree                        |
| Material                  | Aluminium/steel/PMMA             |
| Colour                    | white                            |
| Way of mounting           | Ceiling installation accessories |
| Colour temperature        | 3000 Kelvin                      |
| Colour rendering index    | 80                               |
| Luminous flux             | 690 lm                           |
| Energy efficiency class   | A++                              |
| fastCalcEnabled           | Yes                              |
| ranking                   | 300                              |
| Catalogue page            | BIG WHITE 2017: 725              |

The F-LIGHT is fitted with an integrated 6.35W LED. The recessed light is made of aluminium, steel and plastic and is fitted with a warm-white LED. Next to the white housing colour, an additional cover is available in white, black or chrome. The fire-resistant recessed fitting for standard-compliant increased fire protection in F90 ceilings. A suitable constant current driver providing 350mA is required to operate the recessed fitting. This luminaire contains built-in LED lamps and is available in various beam angles. Optionally, a funnel-shaped or flat decorative frame can be used. EEI: A - A++. The lamps in the luminaire cannot be replaced.