
⁺SLV







ILU

Spot, LED 50mm, 3000K, white, 350mA, 1.2W

| Article number | 115901 |
|-------------------------|---------------------------|
| Feed-in capability | No |
| Lamp included | No |
| Installation diameter | 5 cm |
| Installation depth | 6.5 cm |
| Tilt range | 90 Degree |
| Rotation range | 350 Degree |
| Height | 9.1 cm |
| Diameter | 6 cm |
| Net weight | 0.102 kg |
| Gross weight | 0.16 kg |
| Voltage | 350 Volts |
| Protection class | |
| Beam angle | 24 Degree |
| Material | Aluminium/plastic |
| Colour | white |
| Way of mounting | Recessed ceiling mounting |
| Average lifespan | 25000 Hours |
| Colour temperature | 3000 Kelvin |
| Colour rendering index | 80 |
| Luminous flux | 55 lm |
| Energy efficiency class | A++ |
| fastCalcEnabled | Yes |
| ranking | 300 |
| Catalogue page | MORE WHITE 2017: 127 |

With its eye-catching design, the ILU LED recessed ceiling light is ideal for glare-free accent lighting. The ILU LED comes in black and white and, thanks to its special construction can be telescoped in and outward as well as turned and pivoted. A LED driver with a constant current of 350mA is needed for use.