





SUPROS 78

recessed fitting, LED, 3000K, round, white, 60° lens, 9W

Article number	116311
Max. wattage	9 Watt
Light distribution type 1	Direct
Product family	Supros Mini 750
Feed-in capability	No
Lamp included	Yes
Installation diameter	10.8 cm
Installation depth	8 cm
Height	7.5 cm
Diameter	11.8 cm
Net weight	0.437 kg
Gross weight	0.507 kg
Voltage	220-240 ~50/60 . 250 Volts
Protection class	II
Beam angle	60 Degree
Material	Aluminium
Colour	white
Way of mounting	Ceiling installation
Average lifespan	25000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	700 lm
Energy efficiency class	A++
fastCalcEnabled	Yes
ranking	300
Catalogue page	BIG WHITE 2017: 517

The SUPROS light series impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The widearea reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.