



## QUAD 2 XL

wall light, LED, 3000K, IP44, square, up/down, white, 3.2W

|                           |                            |
|---------------------------|----------------------------|
| Article number            | 232441                     |
| Number of light sources   | 2                          |
| Max. wattage              | 6.4 Watt                   |
| Lamp                      | COB LED module             |
| Light distribution type 1 | direct-indirect            |
| Light distribution type 3 | Axis-symmetric             |
| Feed-in capability        | No                         |
| Lamp included             | No                         |
| Width                     | 5.3 cm                     |
| Height                    | 15 cm                      |
| Depth                     | 10.2 cm                    |
| Net weight                | 1.009 kg                   |
| Gross weight              | 1.08 kg                    |
| Voltage                   | 100-277 ~50/60 . 350 Volts |
| Protection class          | I                          |
| IP-rating                 | IP 44                      |
| Beam angle                | 110 Degree                 |
| Material                  | Aluminium/glass            |
| Colour                    | white                      |
| Way of mounting           | Surface wall mounting      |
| Average lifespan          | 30000 Hours                |
| Colour temperature        | 3000 Kelvin                |
| Colour rendering index    | 80                         |
| Luminous flux             | 580 lm                     |
| Energy efficiency class   | A++                        |
| fastCalcEnabled           | No                         |
| ranking                   | 300                        |
| Catalogue page            | BIG WHITE 2017: 639        |

The QUAD 2 XL wall light is available in several colours, and fitted with a powerful, warm white LED. The electrical connection of the aluminium luminaire is made directly to the 230V mains supply using the built-in driver. Thanks to its IP44 protection class, the luminaire is suitable for outdoor use.

