

DOLIX

low voltage, housing AISI316 stainless steel, 6W 3000K, 12V-25VDC, IP67



Article number	233510
Type of lamp	LED lamp
Lamp	Power LED
Number of light sources	3
Lamp included	Yes
Installation diameter	8.2 cm
Installation depth	10.2 cm
Height	10.6 cm
Diameter	9.2 cm
Net weight	0.67 kg
Gross weight	0.761 kg
Voltage	12 / 24 Volt
Max. wattage	6 Watt
Protection class	III
Beam angle	40 Degree
Material	stainless steel 316
Colour	stainless steel
Way of mounting	recessed ground mounting
Remark 1	100 cm connection lead included
Remark 2	Energy labels in your language are available in the Service Area sub point Download
Average lifespan	25000 Hours
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	360 lm
Suitable for lamps from EEC	A
Suitable for lamps up to EEC	A++
Light distribution type 1	direct

The walkable recessed ground light DASAR LED LV PRO with a round stainless steel housing and glass cover with warm-white, high-performance power LEDs. Rated IP67, the fitting is suitable for outdoor use. The electrical connection is made via a separately available 12V or 24V LED power supply. For simplified mounting, a recessed housing is included. This luminaire contains built-in LED lamps. EEK: A - A++.
The lamps cannot be changed in the luminaire.