



MILOX 2

outdoor floodlight, double-headed, LED, 3000K, IP55, anthracite, 79W

Article number	234315
Max. wattage	79 Watt
Light distribution type 1	Direct
Feed-in capability	No
Lamp included	No
Length	38 cm
Width	11.5 cm
Height	24 cm
Net weight	4.522 kg
Gross weight	4.939 kg
Voltage	230 ~50 Volts
Protection class	I
IP-rating	IP 55
Beam angle	75 Degree
Material	Aluminium/glass
Colour	anthracite
Way of mounting	Floor mounted / wall mounted
Colour temperature	3000 Kelvin
Colour rendering index	80
Luminous flux	7340 lm
Energy efficiency class	A++
Type of plug	IP Schuko plug
fastCalcEnabled	No
ranking	400
Catalogue page	BIG WHITE 2017: 601

MILOX 2, floodlight for professional use. With a tiltable installation bracket and protection class Ip65, the floodlight is suitable for outdoor installation on the wall or on the floor. The electrical connection of the spot, which is available in warm white and neutral white, is made directly by the built-in driver and the connection lead with mains plug to the 230V mains supply. An optional wall bracket, 50 cm or 80 cm, is available for easy wall mounting. This luminaire contains built-in LED lamps. EEI A - A++ The lamps in the luminaire cannot be replaced.